



Contactor 12,5 kvar
K3-18K01
K3-18K10



Contactor 25 kvar
K3-32K00



Contactor 50 kvar
K3-62K00

Putere nominala de operare la 50/60 Hz Cont aux Tensiunea bobinei
Temperatura ambianta Interne Suplim

50°C			60°C			NO	NC	pcs.	220-240V 50Hz ↓
380V 400V kVAr	415V 440V kVAr	660V 690V kVAr	380V 400V kVAr	415V 440V kVAr	660V 690V kVAr				
12,5	13	20	12,5	13	20	1	-	1	K3-18K10 230
12,5	13	20	12,5	13	20	-	1	1	K3-18K01 230
20	22	33	20	22	33	-	-	3 ¹⁾	K3-24K00 230
25	27	41	25	27	41	-	-	3 ¹⁾	K3-32K00 230
33,3	36	55	33,3	36	55	-	-	3 ¹⁾	K3-50K00 230
50	53	82	50	53	82	-	-	3 ¹⁾	K3-62K00 230
75 ²⁾	75 ²⁾	120 ²⁾	60 ²⁾	64 ²⁾	100 ²⁾	-	-	3 ¹⁾	K3-74K00 230



Contact HA 01



Contact HB 11



Contact HN 01

Curent nominal operational			Pentru contactoare	Contacte		Tip		
AC15 230V A	AC15 400V A	AC1 690V A		NO	NC			
6	4	25	K3-18K.. to K3-74K..	-	1	HA01 HB11		
3	2	10	K3-24K00, K3-74K00 pentru montaj lateral	1	1			
3	2	10	K3-18K.. to K3-74K..	1	-	HN10 HN01		
3	2	10	K3-18K.. to K3-74K..	-	1			
AC15 230V A	AC15 400V A	AC1 690V A		NO	NC	EM	LB	
3	2	10		1	-	-	-	HN10
3	2	10		-	1	-	-	HN01