



● BS-912B



● BS-916V



● BS-1018B



● BS-1018R

Item	Unit	BS-912B	BS-916V/BS-916VR	BS-1018B	BS-1018R
Capacity circular @90°	mm	229 (9")	229 (9")	254 (10")	254 (10")
Capacity rectangular @90°	mm	178 × 305 (7" × 8.25")	127 × 405 (5" × 16")	127 × 457 (5" × 18")	160 × 406 (6.3" × 16")
Capacity circular @45°	mm	150 (6")	150 (6")	150 (6")	170 (6.7")
Capacity rectangular @45°	mm	127 × 150 (5" × 6")	150 × 190 (6" × 7.5")	150 × 190 (6" × 7.5")	160 × 190 (6.3" × 7.5")
Blade speed @60Hz	MPM	32,60,88,115	22-122,95-402	35,60,88,115	35,60,88,115
Blade speed @50Hz	MPM	26,50,73,95	18-102,78-335	26,50,73,95	26,50,73,95
Blade size	mm	27 × 0.9 × 2655	27 × 0.9 × 3075	27 × 0.9 × 3280	27 × 0.9 × 3215
Motor power	kw	1.1 1.5HP (3PH), 1.5 2HP (1PH)	1.5 2HP (3PH)	1.5 2HP (3PH)	1.5 2HP (3PH)
Drive		V-belt	V-belt	V-belt	V-belt
Packing size	cm	158 × 62 × 115	180 × 77 × 114	183 × 83 × 115	180 × 77 × 115
N.W./G.W.	kg	230/260	300/360 320/380	310/385	300/360