



SPECIFICATIE TEHNICA AUTOCOLANT STATIC FARA ADEZIV GEKKOFIX

Specificatie produs: "Folie autoadeziva static fara adeziv".

Generalitati: Folia din PVC nu contine cadmiu si plumb, nu prezinta gauri, dungi sau pete. Aspectul este lucios sau mat, stantat si culorile conforme cu standardele.

Hartia: Polyester $\pm 75\mu\text{m}$

Depozitarea: Este recomandata depozitarea la temperaturi de 18-26 grade C.

Masuri de utilizare : Inainte de utilizare, folia trebuie tinuta la temperatura camerei.

Caracteristici material	Valori-Target	Metode
Grosimea foliei	$95 \pm 5\mu\text{m}$ (130 gr/m ²)	DIN 53.353
Rezistenta foliei	58 ± 3	Metoda Hause
Luciu neimprimat	Luciu: >75 Mat: $15 \pm 7\%$	60° Gardner Erichsen
Contractare - pe sticla	Lungime: max 1% Latime : $\pm 0.5\%$	7 zile/ 50 ° C
Toxicitate	Migrarea elementelor listate in standarde sunt sub nivelul maxim recomandat.	BS – EN 71- 3

Unitate de ambalare

Dimensiunile rolelor :

Toleranta :

Diametru :

Nr. role in bax :

Lungime: 1-15 m.

Lungime: -0+2cm.

Rola mica: $\pm 37\text{mm}$.

Rola mica : 6-15 buc.

Latime : 45, 67,5, 90 cm.

Latime : -0+3cm.

Rola mare: $\pm 90\text{mm}$

Rola mare : 1-6 buc.