



Features

- SuperCut 300 saw unit -3/4" inch pitch 11H saw chain
- Patented automatic chain tensioning
- 850 mm (33.5 inch) cut capacity
- High grapple arm gripping force
- Continuous rotation - high capacity IR22 rotator
- Saw bar limiter feature
- Fast replacement of saw bar or chain
- Cushioned cylinders
- Hydraulic snubber for controlled side to side motion
- Unique upper boom link system for simple installation on log loaders, excavators and feller bunchers

Technical Data

Weight	kg	(lb.)	1550	(3410)
Nominal cut capacity	mm	(inches)	850	(33.5)
Maximum gripping width	mm	(inches)	1100	(43.3)
Dimension "A"	mm	(inches)	380	(15.0)
Dimension "B"	mm	(inches)	1101	(43.4)
Dimension "C"	mm	(inches)	2053	(80.8)
Dimension "D"	mm	(inches)	2158	(85.0)
Dimension "E"	mm	(inches)	1443	(56.8)
Dimension "F"	mm	(inches)	1658	(65.3)
Dimension "G"	mm	(inches)	149.35	(5.9)

IR22 Rotator:

Max load capacity	kN	(lbf)	450	(101165)
Torque at 20 MPa (2900 psi)	Nm	(ft.lb.)	3300	(2435)

Saw hydraulic requirements:

Flow	l/min	(gpm)	172 -256	(45 - 67)
Pressure	MPa	(psi)	18 - 27	(2600 - 3900)

0103-7000514-EN