

SCL3711

Contactless reader & NFC enabling accessory



Features

- Multi-protocol 13.56MHz contactless reader:
 - ISO14443 type A & B
 - MIFARE
 - FeliCa™
- optional NFC Peer-to-peer communication
- PC/SC compliant

Your contactless mobile reader & NFC-enabling accessory

With its functional solid mechanical design that has no removable parts that you may loose, SCL3711 is perfect for mobile uses. While being slim, SCL3711 dimensions have been optimized to ensure best RF performance possible with such a form factor.

The state of the art multi-protocol feature set of SCL3711 qualifies it to be used in a wide range of applications such as payment, loyalty and ID schemes, or to enable devices with NFC connectivity.

As a latest generation product, SCL3711 can be supported by SCM's middleware that resides above the PC/SC API and offers better portability of applications and abstraction of smart card related details that need to be handled by applications developed on top of the PC/SC API.

A software development kit is available.

For further information:

http://www.scmmicro.com or sales@scmmicro.com



Contactless Technology

Headquarters

SCM Microsystems GmbH Oskar-Messter-Str. 13 85737 Ismaning, Germany E-mail sales@scmmicro.com Phone +49 89 9595 5000 Fax +49 89 9595 5555

U.S. Office SCM Microsystems, Inc. 1900-B Carnegie Avenue Santa Ana, CA 92705 USA E-mail scmsales@scmmicro.com Phone +1 888 446 9008 Fax +1 888 446 1210

SCM Microsystems Japan, Inc. GoogolPlex Millennium Building 6F 4-4-20 Shiba, Minato-ku, Tokyo, Japan 108-0014 E-mail sales@scmmicro.co.jp Phone +81 3 6414 6611 Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd. Module No. 0506, 0507 & 0508 D' Block South, 5th Floor Tidel Park, 4 Canal Bank Road Taramani Chennai 600113, India E-mail sales@scmmicro.co.in Phone +91 44 2254 0020 Fax +91 44 2254 0029

www.scmmicro.com



SCL3711

Technical Data

Interfaces		
Host	USB	 USB 2.0 full speed PC/SC v2.01 Hardware abstraction layer (HAL) that sits on top of PC/SC API. Common to all SCM readers
Smart Card	contactless	 Antenna ISO/IEC 14443 compliant design Baudrate up to 848 Kbps Supported standards: Type A until ISO/IEC 14443-3 Type B until ISO/IEC 14443-3 ISO/IEC 14443-4 MIFARE: Classic 1K and 4K, Mifare plus, DESFire, Ultralight my-d™ NFC FeliCa™ NFC forum tag type 1, 2, 3, 4 ISO/IEC 18092 peer-to-peer protocol up to 412 Kbps
Human	optical	LED for connection status
Operating Systems		 Windows® 7, Vista, XP, 2000, Server 2003 Mac OS X, Linux or Windows® CEupon demand
Firmware		Not upgradeable
Power	USB	Bus powered
Operating Temperature	[°C]	• -20 - 70
Storage Temperature	[°C]	• -40 - 85
Dimensions	LxWxH[mm]	• 66 x 24 x 8
Weight	[9]	• 10
Approvals		USB, CE, FCC, VCCI, WEEE, RoHS, WHQL Radio Frequency for Japan
Support		Software development kit

^{*}Technical data provided here is subject to changes without notice MIFARE is a registered trademark of NXP Semiconductors B.V. FeliCa is a registered trademark of Sony Corporation my-d™ is a trademark of Infineon Technologies AG.

The SCM Microsystems' Advantage

Trusted Partner

- ASIC (application specific IC) and smart card reader development experience since 1990
- · Innovative solutions more than 50 patents filed
- Reliable high-quality mass production capability more than 15 Mio. reader solutions deployed to date
- · Active role in standardization committees
- Complex project management expertise

 e.g. U.S. Department of Defense CAC program,
 electronic ID applications (ePassport, health card projects, national ID, driver licence)

Support

- · Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

Trusted Products

- Broadest portfolio of security technology products for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions SCM's SmartOS™ firmware and its own ASIC technology allow in Field upgrades and secure your investment