

Anaeston 3000PS Anesthesia machine

Feature

- Dual flow tube with precise output down to 20ml
- Tidal volume compensation for low and minimal flow
- Manual, VCV, PCV, PLV ventilation available
- Autoclavable and latex-free components
- Tool-free maintenance and cleaning
- Built-in 5.7" monochrome TFT monitor
- Reusable CO₂ canister easy to refill and clean
- CE marked



Compact ventilator



Medical CO₂ absorbent, 4.5kg / pack

Specification

Dimension	810x810x1360 mm (WxDxH)
Weight	96 kg
Driven mode	Pneumatically driven, electronically controlled
Gas supply	O ₂ , N ₂ O
Input pressure	280~650 kpa
O₂ flush	35~75 L/min
Power supply	110/230VAC, 60/50HZ
Batter backup	60 minutes
Vaporizer Mount	1, Selectatec™ (Datex-Ohmeda' s trademark)
Agent type	Halothane, Enflurane, Isoflurane, Sevoflurane, Desflurane
Patient type	Adult and pediatric
Tidal volume	20~1500 ml
Ventilation mode	Manual, VCV, PCV, PLV
Value Monitoring	Tidal volume, Minute Volume, Respiratory rate, I:E ratio Pmax, Pmean, Pplat FiO ₂ %
Graphic Monitoring	P-T curve

Alarm

(Audible and visual alarm indication with diagnostic messages for trouble-shooting)	
Alarm silence	120 seconds
Alarm content	High/low Vt, High/low MV, High/low Paw, High/low FiO ₂ , High/low flow Airway Malfunction, Power failure, Low battery and so on