

# COMBICLICK®

## COMBICLICK® backing pads



COMBICLICK® backing pads




This backing pad permits the use of COMBICLICK® tools on all common angle grinders. The cooling slot geometry ensures a high throughput of air, thus significantly reducing thermal loads on the abrasive material and workpiece.

The patented COMBICLICK® mounting system minimizes tool changing times.

### Safety notes:

- The maximum permitted peripheral speed is 80 m/s
- For backing pads with a diameter of 180 mm, do not apply too high a contact pressure in order to prevent overstretching of the backing pad



Description	EAN 4007220	Thread	Suitable for	Suitable for machine types	Max. perm. speed [RPM]	
CC-GT 100 M10	836200	M10	CC dia. 100	Angle grinders 100, spindle M10	15,300	1
CC-GT 115-125 M14	725764	M14	CC dia. 115, CC dia. 125	Angle grinders 115 / 125, spindle M14	13,300	1
CC-GT 115-125 5/8"	725771	5/8	CC dia. 115, CC dia. 125	Angle grinders 115 / 125, spindle 5/8"	13,300	1
CC-GT 180 M14	725788	M14	CC dia. 180	Angle grinders 180, spindle M14	8,500	1
CC-GT 180 5/8"	725795	5/8	CC dia. 180	Angle grinders 180, spindle 5/8"	8,500	1