



BESTRICH TBR TIRES DATA BOOK

BESTRICH >>

SHANDONG TRANSTONE TYRE CO., LTD

Add: NO.39 SHILING ROAD, QINGDAO, CHINA

Tel: 0086-532-55576319 Fax: 0086-532-55576350

E-mail: kevin.liu@transtonetire.com

kevin_lee@transtonetire.com Web: www.transtonetire.com

BESTRICH



INTRO

SHANDONG TRANSTONE TYRE CO., LTD. IS ONE OF THE LEADING TYRE SUPPLIERS IN CHINA, SPECIALIZED IN DISTRIBUTING ALL KINDS OF TYRES, SUCH AS TRUCK AND BUS TYRES, PASSENGER CAR TYRES, OTR TYRES, FORKLIFT TYRES, WHEELS AND TUBES, ETC.

ORGANIZATION

SINCE OUR FOUNDATION IN 2000, WITH THE SUPPORT OF HEADQUARTER IN HEBEI PROVINCE, THE FAST DEVELOPMENT OF EXPORTING OFFICE IN QINGDAO, AND GREATEST SUPPORT FROM ESTEEMED DOMESTIC & OVERSEA CUSTOMERS, TRANSTONE TYRE HAS GAINED A GREAT FAME IN TYRE MARKET.

PRODUCTS

THE MAIN PRIVATE BRANDS OF TRANSTONE COMPANY INCLUDE TRANSTONE(TBR&OTR), KINGRUN(TBR&PCR&OTR), BESTRICH(TBR&PCR&OTR), AND SAFEMAX(TBR&OTR). THESE BRANDS HAVE BEEN WELL KNOWN IN MARKETS SUCH AS AMERICA, MIDDLE EAST, ASIA, RUSSIA ,AND AFRICA. WITH EXCELLENT PATTERN DESIGN AND STABLE QUALITY .OUR BRAND TIRE HAS ENJOYED GREAT FEEDBACK FROM CUSTOMERS ALL OVER THE WORLD.

SERVICE

TRANSTONE COMPANY IS COMMITTED TO HELP CUSTOMERS TO EXPLORE THEIR MARKETS AND PROFIT BY PROVIDING QUALITY PRODUCTS, COMPETITIVE PRICES, AND AFTER-MARKET SERVICES.

CERTIFICATES

TBR: GCC, ECE, DOT, NOM, S-MARK, REACH, SONCAP, AND ISO ETC.

PCR: GCC, ECE, S-MARK, REACH, NOM, AND ISO ETC.

ALL POSITION



B5R78



B5R580



B5R586



ECOMASTER300

STEERING



ECOMASTER100



B5R77



B5R636



B5R617

DRIVING



ECOMASTER200



B5R708



B5R717



B5R768



B5R776



B5R904



B5R947



B5R977





ECOMASTER 100



- Special tread compound for high wear resistance and low heat generation.
- 4 steel belts for excellent performance on rolling and stability.
- 5 ribs for premium handling ability and partial wear resistance.



STEERING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11R22.5	14	14.00	8.25	G	144/142	M	2800/2650	6175/5840	720	105
11R22.5	16	14.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
11R24.5	14	14.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	16	14.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
215/75R17.5	16	12.00	6.00	H	126/124	M	1700/1600	3750/3530	700	100
215/75R17.5	18	12.00	6.00	H	135/133	J	1700/1600	3750/3530	700	100
225/70R19.5	14	12.00	6.75	G	128/126	M	1800/1700	3970/3750	760	110
235/75R17.5	16	12.00	6.75	H	132/130	M	2000/1900	4409/4190	775	115
235/75R17.5	18	12.00	6.75	H	132/130	J	2000/1900	4409/4190	775	115
245/70R19.5	16	12.00	7.50	H	136/134	M	2240/2120	4940/4680	825	120
265/70R19.5	16	12.00	7.50	H	140/138	M	2500/2360	5510/5200	775	115
275/70R22.5	16	14.00	8.25	H	144/141	M	2800/2575	6175/5675	760	110
275/70R22.5	18	14.00	8.25	H	148/145	M	3150/2900	6945/6395	850	125
285/75R24.5	14	14.00	8.25	G	144/141	M	2800/2575	6175/5675	760	110
285/75R24.5	16	14.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	14	14.00	9.00	G	144/141	M	2800/2575	6175/5675	760	110
295/75R22.5	16	14.00	9.00	H	146/143	M	3000/2725	6610/6005	830	120



ECOMASTER 200



- Super deep tread for excellent traction ability and long tyre life.
- 4 steel belts design for excellent performance on rolling and stability.
- Reinforced bead and belts for heavy load capacity.



DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11R22.5	14	21.00	8.25	G	144/142	M	2800/2650	6175/5840	720	105
11R22.5	16	21.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
11R24.5	14	21.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	16	21.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
285/75R24.5	14	21.00	8.25	G	144/141	M	2800/2575	6175/5675	760	110
285/75R24.5	16	21.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	14	21.00	9.00	G	144/141	M	2800/2575	6175/5675	760	110
295/75R22.5	16	21.00	9.00	H	146/143	M	3000/2725	6610/6005	830	120



 ECOMASTER300



- Designed for trailer position only.
- Low rolling resistance and optimum running costs.
- Closed shoulder for irregular wear resistance.

TRAILER

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11R22.5	14	11.00	8.25	G	144/142	M	2800/2650	6175/5840	720	105
11R22.5	16	11.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
11R24.5	14	11.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	16	11.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
285/75R24.5	14	11.00	8.25	G	144/141	M	2800/2575	6175/5675	760	110
285/75R24.5	16	11.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	14	11.00	9.00	G	144/141	M	2800/2575	6175/5675	760	110
295/75R22.5	16	11.00	9.00	H	146/143	M	3000/2725	6610/6005	830	120



BSR77



- The king of abrasion resistance performance with deep tread groove and high pattern density.
- Super steel belt carcass enhances casing strength and load capacity.
- Open shoulder design for enhancing heat dissipation and traction ability.

STEERING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11.00R20	18	16.50	8.00	J	152/149	L	3550/3250	7830/7160	930	135
11R22.5	16	17.50	8.25	H	146/143	M	3000/2725	6610/6005	830	120
12.00R20	20	18.00	8.50	L	156/153	L	4000/3650	8820/8050	900	130
12R22.5	18	18.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
13R22.5	18	20.00	9.75	J	154/151	M	3750/3450	8270/7610	830	120
295/80R22.5	18	17.50	9.00	J	152/149	M	3550/3250	7830/7160	900	130
315/80R22.5	18	18.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20	18.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125



BSR78



- The most popular pattern for different road conditions.
- Special tread compound for high wear resistance and low heat generation.
- Super steel belt carcass enhances casing strength and load capacity.



ALL POSITION

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
6.50R16	12	9.50	5.50F	F	110/105	M	1060/925	2335/2040	670	100
7.00R16	14	10.50	5.50F	G	118/114	M	1320/1180	2910/2600	770	110
7.50R16	14	13.00	6.00G	G	122/118	L	1500/1320	3305/2910	770	110
8.25R16	16	13.00	6.50H	H	128/124	L	1800/1600	3975/3525	770	110
9.00R20	16	15.50	7.00	H	144/142	L	2800/2650	6170/5840	900	130
10.00R20	18	16.50	7.50	J	149/146	L	3250/3000	7160/6610	930	135
11.00R20	18	17.00	8.00	J	152/149	L	3550/3250	7830/7160	930	135
12.00R20	20	16.50	8.50	L	156/153	L	4000/3650	8820/8050	900	130
11R22.5	16	15.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
11R22.5	18	15.00	8.25	J	148/145	M	3150/2900	6945/6395	850	125
11R24.5	14	15.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	16	15.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
12R22.5	18	16.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135



BSR580



- Special tread compound for low heat generation, especially for hot weather condition.
- Big block pattern in the middle of tread for good abrasion resistance.
- Stone rejector for protection of tread.



ALL POSITION

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
12.00R24	20	15.50	8.50	L	160/157	K	4500/4125	9920/9090	900	130



BSR586



- Special tread compound for low heat generation, especially for hot weather condition.
- 3 longitudinal grooves for good handling performance.
- Zigzag groove for better gripping capacity.

ALL POSITION

SIZE	P.R.	PATTERN DEPTH	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
		(mm)					(kg)	(lbs)	(kPa)	(psi)
12.00R24	20	14.50	8.50	L	160/157	K	4500/4125	9920/9090	900	130



BSR617



- Designed for trailer position only.
- Wide closed shoulder for irregular wear resistance.
- Low rolling resistance and optimum running costs.

TRAILER

SIZE	P.R.	PATTERN DEPTH	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
		(mm)					(kg)	(lbs)	(kPa)	(psi)
385/65R22.5	20	15.00	11.75	L	160	K	4500	9920	900	130



BSR636



- Special tread compound for high wear resistance and low heat generation.
- 4 steel belts design for excellent performance on rolling and stability.
- 5 ribs for premium handling ability.

STEERING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11R22.5	16	15.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
12R22.5	18	16.50	9.00	J	152/149	M	3550/3250	7830/7160	930	135
12R22.5	18	16.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
275/80R22.5	16	14.00	8.25	H	149/146	M	3250/3000	7160/6610	850	125
295/80R22.5	18	15.00	9.00	J	152/149	M	3550/3250	7830/7160	900	130
315/60R22.5	16	15.00	9.75	J	152/148	L	3550/3150	7830/6945	900	130
315/70R22.5	18	15.00	9.00	J	152/148	M	3550/3150	7830/6945	830	120
315/80R22.5	18	16.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20	16.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125



BSR708



- Directional pattern for excellent handling performance and drainage performance.
- Super wide tread (270mm) for excellent mileage performance and control performance.
- Deep block pattern for excellent driving ability on wet and dry road conditions.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
315/80R22.5	18	21.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20	21.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125



BSR717



- Wide and deep tread for excellent mileage performance.
- Open shoulder for enhancing heat dissipation and traction ability.
- Reinforced bead and belts for heavy load capacity.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11R22.5	16	20.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
12R22.5	18	20.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
215/75R17.5	16	15.00	6.00	H	126/124	M	1700/1600	3750/3530	700	100
215/75R17.5	18	15.00	6.00	H	126/124	J	1700/1600	3750/3530	700	100
225/70R19.5	14	15.00	6.75	G	128/126	M	1800/1700	3970/3750	760	110
235/75R17.5	16	15.00	6.75	H	132/130	M	2000/1900	4409/4190	775	115
235/75R17.5	18	15.00	6.75	H	132/130	M	2000/1900	4409/4190	775	115
245/70R19.5	16	15.00	7.50	H	136/134	M	2240/2120	4940/4680	825	120
265/70R19.5	16	15.00	7.50	H	140/138	M	2500/2360	5510/5200	775	115
275/80R22.5	16	19.00	8.25	H	149/146	M	3250/3000	7160/6610	850	125
295/80R22.5	18	20.00	9.00	J	152/149	M	3550/3250	7830/7160	900	130
315/70R22.5	18	20.00	9.00	J	152/148	M	3550/3150	7825/6945	830	120
315/80R22.5	18	20.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20	20.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125



BSR768



- Special tread compound for high wear resistance and low heat generation.
- Reinforced bead and belts for heavy load capacity.
- Directional pattern for excellent drainage performance.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
315/80R22.5	18	20.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20	20.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125
13R22.5	18	22.00	9.75	J	154/151	L	3750/3450	8270/7610	830	120



BSR776




- Special tread compound for high wear resistance and long tyre life.
- Large footprint for excellent handling and traction ability.
- Reinforced bead and belts for heavy load capacity.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
12R22.5	18	19.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135



BSR904



- Horizontal blocks for excellent traction ability on rough roads.
- Reinforced bead and belts for heavy load capacity.
- Stone rejector design for the protection of tread.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
7.50R16LT	14	15.50	6.00G	G	122/118	L	1500/1320	3305/2910	770	110
8.25R16LT	16	16.00	6.50H	H	128/124	L	1800/1600	3975/3525	770	110
10.00R20	18	18.00	7.50	J	149/146	L	3250/3000	7160/6610	930	135
11.00R20	18	18.00	8.00	J	152/149	L	3550/3250	7830/7160	930	135
12.00R20	20	19.50	8.50	L	156/153	L	4000/3650	8820/8050	900	130
12.00R24	20	20.00	8.50	L	160/157	K	4500/4125	9920/9090	900	130
325/95R24	22	20.00	8.50	L	160/157	K	4500/4125	9920/9090	900	130



BSR947



- Reinforced bead and 0 degree belt design on tread for over-loading capacity.
- Super deep tread for long tyre life.
- Thicken sidewall for strong carcass.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11.00R20	18	23.00	8.00	J	152/149	E	3550/3250	7830/7160	930	135
12.00R20	20	24.00	8.50	L	156/153	E	4000/3650	8820/8050	900	130



BSR977



- Reinforced bead and 0 degree belt design on tread for over-loading capacity.
- Huge horizontal blocks for excellent traction ability on off road condition.
- Super deep tread for long tyre life.

DRIVING

SIZE	P.R.	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
							(kg)	(lbs)	(kPa)	(psi)
11.00R20	18	24.50	8.00	J	152/149	E	3550/3250	7830/7160	930	135
12.00R20	20	25.50	8.50	L	156/153	E	4000/3650	8820/8050	900	130

SIZE	P.R.	PATTERN	PATTERN DEPTH (mm)	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
								(kg)	(lbs)	(kPa)	(psi)
6.50R16LT	12	BSR78	9.50	5.50F	F	110/105	M	1060/925	2335/2040	670	100
7.00R16LT	14	BSR78	10.50	5.50F	G	118/114	M	1320/1180	2910/2600	770	110
7.50R16LT	14	BSR78	13.00	6.00G	G	122/118	L	1500/1320	3305/2910	770	110
	14	BSR904	15.50	6.00G	G	122/118	L	1500/1320	3305/2910	770	110
8.25R16LT	16	BSR78	13.00	6.50H	H	128/124	L	1800/1600	3975/3525	770	110
	16	BSR904	16.00	6.50H	H	128/124	L	1800/1600	3975/3525	770	110
9.00R20	16	BSR78	15.50	7.00	H	144/142	L	2800/2650	6170/5840	900	130
10.00R20	18	BSR78	16.50	7.50	J	149/146	L	3250/3000	7160/6610	930	135
	18	BSR904	18.00	7.50	J	149/146	L	3250/3000	7160/6610	930	135
11.00R20	18	BSR77	16.50	8.00	J	152/149	L	3550/3250	7830/7160	930	135
	18	BSR78	17.00	8.00	J	152/149	L	3550/3250	7830/7160	930	135
	18	BSR904	18.00	8.00	J	152/149	L	3550/3250	7830/7160	930	135
	18	BSR947	23.00	8.00	J	152/149	E	3550/3250	7830/7160	930	135
	18	BSR977	24.50	8.00	J	152/149	E	3550/3250	7830/7160	930	135
	20	BSR77	18.00	8.50	L	156/153	L	4000/3650	8820/8050	900	130
12.00R20	20	BSR78	16.50	8.50	L	156/153	L	4000/3650	8820/8050	900	130
	20	BSR904	19.50	8.50	L	156/153	L	4000/3650	8820/8050	900	130
	20	BSR947	24.00	8.50	L	156/153	E	4000/3650	8820/8050	900	130
	20	BSR977	25.50	8.50	L	156/153	E	4000/3650	8820/8050	900	130
	20	BSR580	15.50	8.50	L	160/157	K	4500/4125	9920/9090	900	130
12.00R24	20	BSR586	14.50	8.50	L	160/157	K	4500/4125	9920/9090	900	130
	20	BSR904	20.00	8.50	L	160/157	K	4500/4125	9920/9090	900	130
	16	BSR636	15.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
11R22.5	16	BSR717	20.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	16	BSR77	17.50	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	16	BSR78	15.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	18	BSR78	15.00	8.25	J	148/145	M	3150/2900	6945/6395	850	125
	14	ECOMASTER100	14.00	8.25	G	144/142	M	2800/2650	6175/5840	720	105
	16	ECOMASTER100	14.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	14	ECOMASTER200	21.00	8.25	G	144/142	M	2800/2650	6175/5840	720	105
	16	ECOMASTER200	21.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	14	ECOMASTER300	11.00	8.25	G	144/142	M	2800/2650	6175/5840	720	105
	16	ECOMASTER300	11.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	14	BSR78	15.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
	16	BSR78	15.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
	14	ECOMASTER100	14.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
	16	ECOMASTER100	14.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
11R24.5	14	ECOMASTER200	21.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
	16	ECOMASTER200	21.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
	14	ECOMASTER300	11.00	8.25	G	146/143	M	3000/2725	6610/6005	720	105
	16	ECOMASTER300	11.00	8.25	H	149/146	M	3250/3000	7160/6610	830	120
	18	BSR636	16.50	9.00	J	152/149	M	3550/3250	7830/7160	930	135
	18	BSR636	16.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
	18	BSR717	20.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
	18	BSR77	18.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
12R22.5	18	BSR776	19.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
	18	BSR78	16.00	9.00	J	152/149	M	3550/3250	7830/7160	930	135
	18	BSR77	20.00	9.75	J	154/151	M	3750/3450	8270/7610	830	120
	18	BSR768	22.00	9.75	J	154/151	L	3750/3450	8270/7610	830	120
	18	BSR77	20.00	9.75	J	154/151	L	3750/3450	8270/7610	830	120
	18	BSR768	22.00	9.75	J	154/151	L	3750/3450	8270/7610	830	120

SIZE	P.R.	PATTERN	PATTERN DEPTH	RIM	LOAD RATE	LOAD INDEX	SPEED SYMBOL	MAX LOAD		MAX PRESSURE	
			(mm)					(kg)	(lbs)	(kPa)	(psi)
215/75R17.5	16	BSR717	15.00	6.00	H	126/124	M	1700/1600	3750/3530	700	100
	18	BSR717	15.00	6.00	H	126/124	J	1700/1600	3750/3530	700	100
	16	ECOMASTER100	12.00	6.00	H	126/124	M	1700/1600	3750/3530	700	100
	18	ECOMASTER100	12.00	6.00	H	135/133.	J	1700/1600	3750/3530	700	100
225/70R19.5	14	BSR717	15.00	6.75	G	128/126	M	1800/1700	3970/3750	760	110
	14	ECOMASTER100	12.00	6.75	G	128/126	M	1800/1700	3970/3750	760	110
235/75R17.5	16	BSR717	15.00	6.75	H	132/130	M	2000/1900	4409/4190	775	115
	18	BSR717	15.00	6.75	H	132/130	M	2000/1900	4409/4190	775	115
	16	ECOMASTER100	12.00	6.75	H	132/130	M	2000/1900	4409/4190	775	115
	18	ECOMASTER100	12.00	6.75	H	132/130	J	2000/1900	4409/4190	775	115
245/70R19.5	16	BSR717	15.00	7.50	H	136/134	M	2240/2120	4940/4680	825	120
	16	ECOMASTER100	12.00	7.50	H	136/134	M	2240/2120	4940/4680	825	120
265/70R19.5	16	BSR717	15.00	7.50	H	140/138	M	2500/2360	5510/5200	775	115
	16	ECOMASTER100	12.00	7.50	H	140/138	M	2500/2360	5510/5200	775	115
275/70R22.5	16	ECOMASTER100	14.00	8.25	H	144/141	M	2800/2575	6175/5675	760	110
	18	ECOMASTER100	14.00	8.25	H	148/145	M	3150/2900	6945/6395	850	125
275/80R22.5	16	BSR636	14.00	8.25	H	149/146	M	3250/3000	7160/6610	850	125
	16	BSR717	19.00	8.25	H	149/146	M	3250/3000	7160/6610	850	125
285/75R24.5	14	ECOMASTER100	14.00	8.25	G	144/141	M	2800/2575	6175/5675	760	110
	16	ECOMASTER100	14.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	14	ECOMASTER200	21.00	8.25	G	144/141	M	2800/2575	6175/5675	760	110
	16	ECOMASTER200	21.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
	14	ECOMASTER300	11.00	8.25	G	144/141	M	2800/2575	6175/5675	760	110
	16	ECOMASTER300	11.00	8.25	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	14	ECOMASTER100	14.00	9.00	G	144/141	M	2800/2575	6175/5675	760	110
	16	ECOMASTER100	14.00	9.00	H	146/143	M	3000/2725	6610/6005	830	120
	14	ECOMASTER200	21.00	9.00	G	144/141	M	2800/2575	6175/5675	760	110
	16	ECOMASTER200	21.00	9.00	H	146/143	M	3000/2725	6610/6005	830	120
	14	ECOMASTER300	11.00	9.00	G	144/141	M	2800/2575	6175/5675	760	110
	16	ECOMASTER300	11.00	9.00	H	146/143	M	3000/2725	6610/6005	830	120
295/80R22.5	18	BSR636	15.00	9.00	J	152/149	M	3550/3250	7830/7160	900	130
	18	BSR717	20.00	9.00	J	152/149	M	3550/3250	7830/7160	900	130
	18	BSR77	17.50	9.00	J	152/149	M	3550/3250	7830/7160	900	130
315/60R22.5	16	BSR636	15.00	9.75	J	152/148	L	3550/3150	7830/6945	830	120
315/70R22.5	18	BSR636	15.00	9.00	J	152/148	M	3550/3150	7825/6945	830	120
	18	BSR717	20.00	9.00	J	152/148	M	3550/3150	7825/6945	830	120
315/80R22.5	18	BSR636	16.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
	20	BSR636	16.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125
	18	BSR717	20.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
	20	BSR717	20.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125
	18	BSR768	20.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
	20	BSR768	20.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125
	18	BSR77	18.00	9.00	J	154/151	M	3750/3450	8270/7610	830	120
	20	BSR77	18.00	9.00	L	156/150	M	4000/3350	8820/7385	850	125
	18	BSR708	21.00	9.00	J	154/151.	M	3750/3450	8270/7610	830	120
	20	BSR708	21.00	9.00	L	156/150.	M	4000/3350	8820/7385	850	125
325/95R24	22	BSR904	20.00	8.50	L	160/157	K	4500/4125	9920/9090	900	130
385/55R22.5	20	BSR686	15.00	12.25	L	160	K	4500	9920	900	130
385/65R22.5	20	BSR617	15.00	11.75	L	160	K	4500	9920	900	130

BESTRICH



WARRANTY

Every tyre purchased from SHANDONG TRANSTONE TYRE CO., LTD(Transtone tyre) and bearing our brand names-BESTRICH TRANSTONE SAFEMAX KINGRUN are warranted by this warranty policy.

The manufacturer/Transtone tyre assures the customer by offering warranty against products failures attributed to deficiency in design, materials & workmanship. Compensation to the customer is offered equivalent to the value of the remaining life of the product, which has failed due to manufacturing defect.

The Warranty Policy & Procedure can be documented as under:

LIMITED WARRANTY:

The compensation amount will be determined by multiplying the Current Adjustment Base Price (C.A.B.P.) by the percentage of tread depth remaining on the returned tyre.

The cost of mounting, balancing and any other service charges should be paid by owner.

$$\text{Compensation Amount} = \text{C.A.B.P.} \times \frac{\text{Tread Depth Remaining on Returned Tire}}{\text{Tread Depth on New Tire}}$$

PROCEDURE:

- The customer shall report to the manufacturer the details of the product, which has failed due to manufacturing defect in the claim form, along with two pictures of the failed product showing the defect and serial number in the product.
- On receipt of the claim form & the pictures of the failed product, the manufacturer will offer compensation based on the report or request the customer to hold the failed product for examination by their technical expert whose visit shall be arranged within one month from the date of the claim form if needed.
- Credit against the approved claims shall be given in next consignment.
- Name & address including e-mail id, of the Manufacturer's representative. to whom the claim forms are to be sent should be mentioned on the claim form.

PRESSURE

Under-inflation can lead to a failure. It results in unnecessary tyre stress, irregular wear, loss of control and accidents. A tyre can lose up to half of its air pressure and not appear to be flat!

ALIGNMENT

A bad jolt from hitting a curb or pothole can throw your front end out of alignment and damage your tires. Have a tire dealer check your alignment periodically to ensure that your tyres are properly aligned.

TREAD

Advanced and unusual wear can reduce the ability of tread to grip the road in adverse conditions. Visually check your tyres for uneven wear, looking for high and low areas or unusually smooth areas. Also check for signs of damage.



Dealer's Information

Log onto <http://www.transtonetire.com> for more information about tyre details.