

| | | P 300 | P 500 | P 800 | P 1000 | P 1500 | P 2000 | P 2500 | P 3000 | P 5000 |
|--|------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Capacity | L | 300 | 500 | 800 | 1000 | 1500 | 2000 | 2500 | 3000 | 5000 |
| Diameter D ø /with insulation ø _i | mm | 550/750 | 650/850 | 790/990 | 790/990 | 1000/1200 | 1200/1400 | 1200/1400 | 1400/1600 | 1600/1800 |
| Height h /with insulation h _i | mm | 1410/1460 | 1610/1660 | 1860/1910 | 2040/2090 | 2150/2220 | 2132/2182 | 2482/2532 | 2246/2296 | 2940/2990 |
| Min. vertical clearance | mm | 1430 | 1640 | 1900 | 2075 | 2220 | 2200 | 2542 | 2332 | 3066 |
| Operating pressure/Max. buffer temperature | bar/°C | 3/95 | 3/95 | 3/95 | 3/95 | 3/95 | 3/95 | 3/95 | 3/95 | 3/95 |
| Recommended boiler size, connected to the buffer | kW | 6-10 | 10-17 | 15-27 | 18-33 | 27-50 | 36-67 | 45-83 | 55-100 | 91-167 |
| Thermometer | | optional | | | | | | | | |
| Coating with insulation (optional) | | 100 mm soft PU | | | | | | | | |
| Weight Buffer /Insulation | kg | 60/9,5 | 90/12,3 | 118/16,4 | 133/18 | 206/23,2 | 273/26,5 | 305/30 | 402/35 | 585/40 |
| Sensor sleeve | A, mm G½" | 410 | 410 | 570 | 580 | 875 | 920 | 920 | 910 | 951 |
| Electric heating element | B, mm G1½" | 760 | 790 | 920 | 1130 | 1130 | 1170 | 1170 | 1184 | 1505 |
| Sensor sleeve | C, mm G½" | 1060 | 1120 | 1290 | 1500 | 1500 | 1645 | 1645 | 1660 | 2001 |
| Air vent sleeve | D, mm G1½" | 1410 | 1610 | 1860 | 2040 | 2150 | 2132 | 2482 | 2246 | 2938 |
| Boiler heat carrier inlet | E, mm G1½" | 1170 | 1370 | 1573 | 1742 | 1808 | 1775 | 2126 | 1797 | 2438 |
| Heat carrier inlet | F, mm G1½" | | | 1390 | 1520 | 1635 | | | | |
| Sensor sleeve | G, mm G½" | 1010 | 1120 | 1290 | 1450 | 1525 | 1625 | 1625 | 1590 | 2231 |
| Boiler heat carrier | H, mm G1½" | 880 | 990 | | | 1305 | 1420 | | 1474 | 2115 |
| Boiler heat carrier | J, mm G1½" | 770 | 880 | 980 | 1060 | 1085 | 1170 | 1420 | 1184 | 1735 |
| Additional sleeve | K, mm | | | | | G½"/975 | | G1½"/1170 | | |
| Heat carrier inlet | L, mm G1" | 660 | 770 | 820 | 880 | 895 | 980 | 980 | 1082 | 1373 |
| Boiler heat carrier | M, mm G1½" | 540 | 620 | 670 | 730 | 765 | 735 | 735 | 864 | 1155 |
| Sensor sleeve | N, mm G½" | 420 | 460 | 465 | 495 | 520 | 500 | 500 | 610 | 691 |
| Heat carrier outlet | O, mm G1" | 260 | 250 | 310 | 310 | 375 | 380 | 380 | 477 | 518 |
| Boiler heat carrier outlet | P, mm G1½" | 150 | 150 | 170 | 170 | 235 | 230 | 230 | 344 | 385 |