

**MOTOCULTOR PRORUN PT-750A****SPECIFICATIILE TEHNICE**

PRODUCATOR	Prorun Power Equipment
IMPORTATOR	Prorun Europe Corporation
ADANCIMEA DE LUCRU CU FREZE	15 - 33 cm
LATIMEA DE LUCRU CU FREZE	60 - 90 cm
VITEZA DE ROTATIE A FREZELOR	120 rpm
CUTIE DE VITEZE	6 viteze (2+1 usor / 2+1 greu)
PRIZA DE PUTERE	Nu
REZERVOR DE CARBURANT	3.6 L
REZERVOR ULEI MOTOR	0.6 L (SAE30)
REZERVOR ULEI TRANSMISIE	0.9 L (T90)
CONSUM ESTIMAT DE CARBURANT	500 ml / h
TIP TRANSMISIE (MOTOR - C.V.)	Curea
TIP TRANSMISIE (C.V-FREZE)	Pinioane cu lant dublu in baie de ulei
SISTEM REGLARE ADANCIME DE LUCRU	Da
MANER REGLABIL	Da, inaltime / lateral
SUPRAFATA DE LUCRU RECOMANDATA	Sub 10.000 mp

MOTOR

MODEL / CARBURANT	168F / Benzina
RACIRE	Aer
CARACTERISTICI	1 cilindru / 4 timpi / ax orizontal
CILINDREE	212 cm ³
PUTERE	7 CP / 3600 rpm
MOD DE PORNIRE	Demaror manual cu recul
SENZOR ULEI	Da

AMBALAJUL SI ALTELE

GREUTATE NETA	72 kg
FREZE (MAX.)	3 segmente / 24 cutite
FREZE SEGMENTABILE	1 Dreapta / 1 Stanga
ROTI DE CAUCIUC	4.00-8 tip balon

PRORUN**MOTOCULTOR PRORUN PT-750A****SPECIFICATIILE TEHNICE**

PRODUCATOR	Prorun Power Equipment
IMPORTATOR	Prorun Europe Corporation
ADANCIMEA DE LUCRU CU FREZE	15 - 33 cm
LATIMEA DE LUCRU CU FREZE	60 - 90 cm
VITEZA DE ROTATIE A FREZELOR	120 rpm
CUTIE DE VITEZE	6 viteze (2+1 usor / 2+1 greu)
PRIZA DE PUTERE	Nu
REZERVOR DE CARBURANT	3.6 L
REZERVOR ULEI MOTOR	0.6 L (SAE30)
REZERVOR ULEI TRANSMISIE	0.9 L (T90)
CONSUM ESTIMAT DE CARBURANT	500 ml / h
TIP TRANSMISIE (MOTOR - C.V.)	Curea
TIP TRANSMISIE (C.V-FREZE)	Pinioane cu lant dublu in baie de ulei
SISTEM REGLARE ADANCIME DE LUCRU	Da
MANER REGLABIL	Da, inaltime / lateral
SUPRAFATA DE LUCRU RECOMANDATA	Sub 10.000 mp

MOTOR

MODEL / CARBURANT	168F / Benzina
RACIRE	Aer
CARACTERISTICI	1 cilindru / 4 timpi / ax orizontal
CILINDREE	212 cm ³
PUTERE	7 CP / 3600 rpm
MOD DE PORNIRE	Demaror manual cu recul
SENZOR ULEI	Da

AMBALAJUL SI ALTELE

GREUTATE NETA	72 kg
FREZE (MAX.)	3 segmente / 24 cutite
FREZE SEGMENTABILE	1 Dreapta / 1 Stanga
ROTI DE CAUCIUC	4.00-8 tip balon

PRORUN**MOTOCULTOR PRORUN PT-750A****SPECIFICATIILE TEHNICE**

PRODUCATOR	Prorun Power Equipment
IMPORTATOR	Prorun Europe Corporation
ADANCIMEA DE LUCRU CU FREZE	15 - 33 cm
LATIMEA DE LUCRU CU FREZE	60 - 90 cm
VITEZA DE ROTATIE A FREZELOR	120 rpm
CUTIE DE VITEZE	6 viteze (2+1 usor / 2+1 greu)
PRIZA DE PUTERE	Nu
REZERVOR DE CARBURANT	3.6 L
REZERVOR ULEI MOTOR	0.6 L (SAE30)
REZERVOR ULEI TRANSMISIE	0.9 L (T90)
CONSUM ESTIMAT DE CARBURANT	500 ml / h
TIP TRANSMISIE (MOTOR - C.V.)	Curea
TIP TRANSMISIE (C.V-FREZE)	Pinioane cu lant dublu in baie de ulei
SISTEM REGLARE ADANCIME DE LUCRU	Da
MANER REGLABIL	Da, inaltime / lateral
SUPRAFATA DE LUCRU RECOMANDATA	Sub 10.000 mp

MOTOR

MODEL / CARBURANT	168F / Benzina
RACIRE	Aer
CARACTERISTICI	1 cilindru / 4 timpi / ax orizontal
CILINDREE	212 cm ³
PUTERE	7 CP / 3600 rpm
MOD DE PORNIRE	Demaror manual cu recul
SENZOR ULEI	Da

AMBALAJUL SI ALTELE

GREUTATE NETA	72 kg
FREZE (MAX.)	3 segmente / 24 cutite
FREZE SEGMENTABILE	1 Dreapta / 1 Stanga
ROTI DE CAUCIUC	4.00-8 tip balon