

AGRIALLE 10W30

MULTIFUNCTIONAL LUBRICANT FOR AGRICULTURAL TRACTORS

120072/12.17

Rev. 2

DESCRIPTION & APPLICATIONS

AGRIALLE, a STOU (Super Tractor Oil Universal) lubricant, is used for the lubrication of any mechanism of agricultural machines : tractors, combine harvesters.

This multifunctional lubricant is recommended because it allows a rationalisation of supply and therefore prevents against any risk of error.

ADVANTAGES

- Multifunctional : engines, hydraulic, mechanical transmissions, wet brakes.
- Viscosity has been studied for an easy start at low temperatures and for a quick transmission of hydraulic control.
- Well-adapted to load which can be found on mechanical transmissions of these machines.

PERFORMANCES

Satisfies to the following specifications:

ACEA E4-08/E7-08

ALLISON C4

API CI-4/GL4

API GL5 (low speed, high torque)

CAT TO2

Ford M2C 159B

JD J20A/J20C/J27A

MF M1139/M1141/M1144/M1145

New Holland 82009202

NH 410B

ZF-TE-ML 06B/06C/07B

AGRIALLE 10W30

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	10W30
Specific gravity at 15°C	kg/m ³	NFT 60101	890
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	64
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	102
Viscosity index	-	NFT 60136	148
Viscosity CCS at -25°C	mPa.s	ASTM D2602	5258
Flash point	°C	ISO 2719	234
Pour point	°C	NFT 60105	-36
Sulphated ash content	% wheight	NF T 60143	1,47
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	12,6

The average values are given for information only.