



## EXSTRO FLEX® Xdur



### Proprietati

|                          |                    |
|--------------------------|--------------------|
| Rezistenta la compresie  | 1250N              |
| Rezistenta la impact     | 6J                 |
| Temperatura minima       | -40 °C             |
| Temperatura maxima       | +105 °C            |
| Rezistenta la indoire    | flexibil           |
| Caracteristici electrice | izolator           |
| Proprietati ardere       | Nu propaga flacara |

HF (halogen free)

Fara degajari de gaze toxice

Rezistenta la razele solare  
(UV): 50 ani

Flexibilitate foarte buna

### Lista de articole

| Tip | Numar articol | Diametru exterior<br>(mm) | Diametru interior<br>(mm) | Lungime pe colac<br>(m) | Lungime pe palet<br>(m) |
|-----|---------------|---------------------------|---------------------------|-------------------------|-------------------------|
| 16  | 13101016      | 16 +0/-0,5                | 10,5 +/- 0,3              | 50                      | 5500                    |
| 20  | 13101020      | 20 +0/-0,5                | 13,5 +/- 0,3              | 50                      | 3750                    |
| 25  | 13101025      | 25 +0/-0,5                | 18,0 +/- 0,4              | 50                      | 2600                    |
| 32  | 13101032      | 32 +0/-0,5                | 24,1 +/- 0,4              | 50                      | 1200                    |