


Product information



Hotraco
—Agri—



Hotraco Agri BV
Stationsstraat 142
5963 AC Hegelsom
Tel +31 (0)77 327 50 20
Fax +31 (0)77 327 50 21
info@hotraco.com
www.hotraco.com

PTC





Temperature sensor for Iris, Sirius

PTC

Temperature sensor
Product information

General

The PTC is a two-wire temperature sensor with shielding and can be used in different applications. Therefore the PTC is available in different encasings. The sensors can be integrated in configurations with IRIS and SIRIUS computers.

PTC	PTC-6 / 15	PTC-W	PTC-BU
			
Room temperature	Floor temperature	Water temperature	Outside temperature

Sensor				
Material	Stainless steel	Stainless steel	Brass-nickled plated	Stainless steel
Dimensions	Ø 6 mm x 45 mm	Ø 6 mm x 45 mm	Ø 10 mm x 100 mm	Ø 6 mm x 45 mm
Screw thread	-	-	1/2" 15 mm	-
Cable length	250 mm	6 m / 15 m	250 mm	250 mm

Encasing				
Material	PVC	-	Aluminium	PVC
Dimensions	75 x 75 x 35 mm	-	58 x 64 x 36 mm	Ø 60/140 x 210mm

Technical specifications

Temperature range	:	-50 °C to +100 °C
Tolerance	:	± 1%
Wiring	:	PVC-cable blue 2 x 0,34 mm ² + shield
Resistance temperature	:	1000 Ω at 25 °C (approx. 815 Ω (0 °C) + 7,7 Ω/°C)