LUBING

LUBING Touch Control



Main facts at a glance: **LUBING Touch Control**

LUBING Touch Controllers are distinguished by their intelligent system configurations and intuitive operating features. Frequently used functions are integrated as direct-access functions. Less often used and administrative functions are placed in subordinate menus. Basically, pictograms and simple menu structures ensure that all required functions can be understood and activated quickly and easily.

Status messages and instructions are displayed in context on the interactive display screen, and quide users through operations in a logical sequence. Controller functions are additionally secured by an integrated alarm function.

Operating functions can be expanded via CAN Bus. Updates are performed via SD card. A data logging functions can be integrated as an option.

Clear symbols, simple menu structures

LUBING Touch Control is easy to use. The ergonomically designed menu interface supports an intuitive grasp of features and capabilities.

The main functions are made directly accessible by simple pictograms:



On/Off



Automatic



Home



Dust binding



Menu



Timer

Versions

LUBING Touch Controllers are available in several different versions. The version of the controller is printed on the front foil, and starts with "LC".

List of available versions:

| Designation | Item | Application for the Top-Climate-System |
|---------------|------|---|
| LC-1 | 7740 | 1 house, without sensors |
| LC-2 | 7741 | 2 houses, without sensors |
| LCS-1 | 7742 | 1 houses, with sensors |
| LCS-2 | 7743 | 2 houses, with sensors |
| LCM | 7744 | Multi house controller for max. 8 boxes |
| LCM vario | 7745 | Multi house controller for max. 8 boxes for pump units with frequency converter |
| Extension box | 7750 | Extension box for LCM and LCM vario for 8 further boxes (max. 4 extension boxes per controller) |

These versions are designed for use with supply voltages ranging from 90 to 264 V 50/60 Hz.

For further information: www.lubing.com

Technical modifications reserved.



Drinking-Systems Conveyor-Systems **Climate-Systems**

LUBING Maschinenfabrik GmbH & Co. KG

Lubingstraße 6 · 49406 Barnstorf (Germany)

Tel.: +49 (0) 54 42 - 98 79-0 · Fax: +49 (0) 54 42 - 98 79-33

www.lubing.com · info@lubing.com