

## CLUSTER PU D

### Furtun refulare flat din poliuretan



Furtun utilizat pentru aplicatii grele in constructii, agricultura si aplicatii industriale. Rezistenta mare la uzura pentru ca furtunul este construit in totalitate din PU.

Exterior:	PU
Interior:	PU
Insertii:	Textile
Numar insertii:	1
Culoare exterior:	Negru
Culoare interior:	Negru

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1010182	76	81.6	16	50		-50 - +75°C		100	750
1010180	90	95.6	14	40		-50 - +75°C		100	950
1010181	102	108	14	40		-50 - +75°C		100	1050
1010193	110	116	10	30		-50 - +75°C		100	1150
1010185	127	133	10	30		-50 - +75°C		100	1400
1010188	152	158	10	30		-50 - +75°C		100	1650
1010190	203	209	8	24		-50 - +75°C		100	2200
1010191	254	260.4	7	21		-50 - +75°C		100	2850
1010194	305	311.6	5	15		-50 - +75°C		100	3500
1010195	356	364.6	4	12		-50 - +75°C		100	5600