

BATUS D**Furtun refulare flat din cauciuc cu striatii**

Furtun utilizat pentru apa si aplicații cu aer comprimat.

Exterior:	NBR
Interior:	NBR
Insertii:	Textil sintetic
Numar insertii:	1
Culoare exterior:	Negru
Culoare interior:	Negru
Norma:	DIN 14811 : 2008 Clasa 3

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1010701	20		16	50		-40 - +100°C		100	195
1010702	25		16	50		-40 - +100°C		100	225
1010708	32		16	50		-40 - +100°C		100	290
1010703	38		16	50		-40 - +100°C		100	310
1010724	45		16	50		-40 - +100°C		100	355
1010704	52		16	50		-40 - +100°C		100	385
1010705	65		16	50		-40 - +100°C		100	500
1010706	75		16	50		-40 - +100°C		100	680
1010709	102		8	35		-40 - +100°C		100	995
1010713	110		8	35		-40 - +100°C		100	1100
1010715	125		8	35		-40 - +100°C		100	1350
1010716	154		8	35		-40 - +100°C		100	1650
1010721	203		7	30		-40 - +100°C		100	2250