

CHONDRIET M D

Furtun refulare flat din cauciuc



Furtun utilizat pentru aplicatii grele in constructii, agricultura si aplicatii industriale.

Exterior:	NBR
Interior:	SBR
Insertii:	Poliester
Numar insertii:	1
Culoare exterior:	Negru
Culoare interior:	Negru

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1010417	19		20	60		-30 - +80 °C		40	170
1010401	25		20	60		-30 - +80 °C		40	210
1010402	32		20	60		-30 - +80 °C		40	260
1010403	38		20	60		-30 - +80 °C		40	300
1010404	42		20	60		-30 - +80 °C		40	340
1010405	45		20	60		-30 - +80 °C		40	380
1010406	52		17	50		-30 - +80 °C		40	450
1010408	70		17	50		-30 - +80 °C		40	670
1010409	75		17	50		-30 - +80 °C		40	720
1010410	90		13	40		-30 - +80 °C		40	920
1010411	102		13	40		-30 - +80 °C		40	1010
1010412	110		12	35		-30 - +80 °C		40	1310
1010413	125		10	30		-30 - +80 °C		40	1480
1010414	152		10	30		-30 - +80 °C		40	1720