

ALTAIR EN ISO Ω /T D
EN ISO 6134 Cat. A tip 1
Furtun abur de joasa presiune din cauciuc


Furtun utilizat pentru abur saturat pana la temperatura de 165 °C , la o presiune maxima de lucru de 6 bar.

Rezistenta la caldura, ozon , intemperii uzura.

Prevazut la exterior cu punctuatii antispargere.

Disponibil si pe culoarea rosie.

Exterior:	EPDM
Interior:	EPDM
Insertii:	Textil sintetic
Numar insertii:	2
Culoare exterior:	Negru
Culoare interior:	Negru
Interior electroconductiv:	$R < 10^6 \Omega$
Exterior electroconductiv:	$R < 10^6 \Omega$
Norma:	EN ISO 6134 TYP 1A

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1020071	13	25	6	60		-40 - +165°C		40	430
1020072	16	30	6	60		-40 - +165°C		40	600
1020073	19	33	6	60		-40 - +165°C		40	680
1020074	25	40	6	60		-40 - +165°C		40	900
1020075	32	48	6	60		-40 - +165°C		40	1100
1020076	38	54	6	60		-40 - +165°C		40	1400
1020077	50	68	6	60		-40 - +165°C		40	2010