

PARALLAX NEO1
Furtun cauciuc cu un perete pentru aspiratie si ventilatie


Furtun aspiratie si ventilatie , foarte flexibil ,ignifug utilizat pentru transportul de aer si gaze cu temperaturi ridicate. Cu un singur perete.

Exterior: CR
 Interior: CR
 Culoare exterior: Negru
 Culoare interior: Negru
 Spirala : Da

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1120101	13		1.7	0	52	-35 - +135°C	8	4	100
1120102	19		1.6	0	51	-35 - +135°C	8	4	110
1120103	26		1.6	0	51	-35 - +135°C	8	4	120
1120104	32		1.4	0	50	-35 - +135°C	10	4	140
1120105	38		1.3	0	50	-35 - +135°C	12	4	170
1120106	41		1.3	0	48	-35 - +135°C	13	4	200
1120107	44		1.2	0	46	-35 - +135°C	14	4	210
1120108	51		1.2	0	43	-35 - +135°C	16	4	250
1120109	57		1.1	0	41	-35 - +135°C	18	4	280
1120110	60		1.1	0	40	-35 - +135°C	20	4	300
1120111	65		1.1	0	38	-35 - +135°C	22	4	340
1120112	70		1.1	0	36	-35 - +135°C	24	4	360
1120113	76		1.1	0	34	-35 - +135°C	27	4	410
1120114	80		1	0	32	-35 - +135°C	28	4	440
1120115	83		1	0	31	-35 - +135°C	28	4	460
1120116	90		1	0	30	-35 - +135°C	29	4	490
1120117	95		0.9	0	28	-35 - +135°C	32	4	560
1120118	102		0.9	0	26	-35 - +135°C	35	4	650
1120119	108		0.9	0	24	-35 - +135°C	38	4	680
1120120	110		0.9	0	24	-35 - +135°C	38	4	690
1120121	114		0.9	0	22	-35 - +135°C	40	4	710
1120122	120		0.8	0	20	-35 - +135°C	43	4	760
1120123	127		0.8	0	17	-35 - +135°C	46	4	800
1120124	130		0.8	0	17	-35 - +135°C	47	4	820
1120126	140		0.7	0	15	-35 - +135°C	48	4	900

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1120127	152		0.7	0	14	-35 - +135°C	51	4	990
1120129	160		0.6	0	13	-35 - +135°C	53	4	1050
1120128	165		0.6	0	12	-35 - +135°C	55	4	1080
1120103	180		0.6	0	11	-35 - +135°C	60	4	1190
1120130	203		0.5	0	7	-35 - +135°C	68	4	1330
1120131	229		0.4	0	6	-35 - +135°C	84	4	1480
1120132	254		0.4	0	4	-35 - +135°C	102	4	1680
1120133	305		0.2	0	2	-35 - +135°C	123	4	2050