

BELINDA AIR**Furtun cauciuc pentru aer comprimat**

Furtun utilizat pentru aer comprimat, apa si produse non-agresive.

| | |
|-------------------|---------|
| Exterior: | NR/SBR |
| Interior: | NR/SBR |
| Insertii: | Textile |
| Numar insertii: | 1 |
| Culoare exterior: | Negru |
| Culoare interior: | Negru |

| Articol Nr. | Ø Int. mm | Ø Ext. mm | P.N. bar | P.S. bar | Vacum % | Temp. °C | R.C. mm | Lungime m | Greutate g/m |
|-------------|-----------|-----------|----------|----------|---------|-------------|---------|-----------|--------------|
| 1100130 | 6 | 13 | 20 | 60 | | -20 - +80°C | | 50 | 140 |
| 1100132 | 8 | 15 | 20 | 60 | | -20 - +80°C | | 50 | 190 |
| 1100134 | 10 | 18 | 20 | 60 | | -20 - +80°C | | 50 | 230 |
| 1100136 | 13 | 21 | 20 | 60 | | -20 - +80°C | | 50 | 320 |
| 1100137 | 16 | 25 | 20 | 60 | | -20 - +80°C | | 50 | 430 |
| 1100140 | 19 | 29 | 20 | 60 | | -20 - +80°C | | 50 | 570 |
| 1100141 | 25 | 36 | 20 | 60 | | -20 - +80°C | | 50 | 740 |