

CYGNUS

Furtun compresor din plastic



Furtun utilizat pentru compresoare aer, apa si substante chimice usoare.

Exterior:	PVC
Interior:	PVC
Insertii:	Textile
Numar insertii:	1
Culoare exterior:	Transparent
Culoare interior:	Transparent
Norma:	EU 10/2011 A,B,C,D2, KTW

Articol Nr.	∅ Int. mm	∅ Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
10428	5	8	20	60		-20 - +60 °C		50	42
10407	6	11	20	60		-20 - +60 °C		50	84
10441	6	12	20	60		-20 - +60 °C		50	103
10408	8	13	20	60		-20 - +60 °C		50	100
10442	8	14	20	60		-20 - +60 °C		50	126
10409	9	15	20	60		-20 - +60 °C		50	138
10443	10	16	20	60		-20 - +60 °C		50	149
10436	12	18	12	36		-20 - +60 °C		50	172
10412	13	19	12	36		-20 - +60 °C		50	184
10414	16	22	10	30		-20 - +60 °C		50	221
10415	19	26	10	30		-20 - +60 °C		50	296
10440	19	27	10	30		-20 - +60 °C		50	348
10416	25	33	8	24		-20 - +60 °C		50	436
10418	30	38	7	21		-20 - +60 °C		50	514
10419	32	42	7	21		-20 - +60 °C		25	695
10420	38	48	6	18		-20 - +60 °C		25	808
10421	50	60	5	15		-20 - +60 °C		25	1032