



PUR L EL 10 4 Ω

Furtun din poliuretan pentru aspiratie si ventilatie

Furtun electro conductiv , rezistent la uzura, usor si flexibil. Furtun utilizat pentru transportul de granule, rumegus, praf, vapori de ulei, etc.

Exterior: PU
Interior: PU
Culoare exterior: Transparent
Culoare interior: Transparent
Spira: Da
Interior electro conductiv: $R < 10^4 \Omega$
Exterior electro conductiv: $R < 10^4 \Omega$
Norma: TRBS 2153 (Zone 0, 20)

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
341723	25		3.2	0	79	-40 - +100°C	31	15	250
341715	32		2.5	0	71	-40 - +100°C	40	15	350
341726	38		2.1	0	66	-40 - +100°C	46	15	390
341733	40		2.1	0	66	-40 - +100°C	48	15	400
341731	45		1.8	0	59	-40 - +100°C	53	15	420
341713	50		1.7	0	52	-40 - +100°C	58	15	450
341725	55		1.5	0	44	-40 - +100°C	63	15	510
341724	60		1.4	0	44	-40 - +100°C	68	15	530
341714	65		1.3	0	37	-40 - +100°C	73	15	640
341730	70		1.1	0	37	-40 - +100°C	78	15	680
341734	75		1.1	0	29	-40 - +100°C	84	15	720
341716	80		1	0	29	-40 - +100°C	88	15	760
341735	90		0.8	0	22	-40 - +100°C	99	15	880
341717	100		0.8	0	22	-40 - +100°C	110	10	950
341732	110		0.7	0	22	-40 - +100°C	119	10	1030
341722	115		0.7	0	22	-40 - +100°C	124	10	1060
341736	120		0.7	0	22	-40 - +100°C	129	10	1120
341718	125		0.7	0	22	-40 - +100°C	135	10	1180
341737	130		0.6	0	22	-40 - +100°C	139	10	1200
341719	140		0.6	0	15	-40 - +100°C	149	10	1380
341781	150		0.6	0	15	-40 - +100°C	161	10	1480
341720	160		0.6	0	15	-40 - +100°C	170	10	1740
341738	170		0.4	0	15	-40 - +100°C	180	10	1800
341739	175		0.4	0	15	-40 - +100°C	185	10	1850
341740	180		0.4	0	15	-40 - +100°C	190	10	1900
341721	200		0.4	0	15	-40 - +100°C	214	10	2300