

PARSEC
Furtun TPE pentru aspiratie si ventilatie

Furtun de termoplastic extrem de flexibil pentru transportul aer, gaze, vapori, vapori de vopsea etc.

Special construit sa reziste la aer umed si fierbinte la temperaturi de până la 130°C.

Exterior:	TPE
Interior:	TPE
Insertii:	Poliester
Numar insertii:	1
Culoare exterior:	Negru
Culoare interior:	Negru
Spira:	Da



Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1120029	20		0.5	0	25	-40 - +150°C	20	10	80
1120001	25		0.5	0	20	-40 - +150°C	25	10	90
1120002	32		0.4	0	20	-40 - +150°C	30	10	140
1120003	38		0.4	0	15	-40 - +150°C	38	10	150
1120026	40		0.4	0	15	-40 - +150°C	40	10	160
1120005	50		0.4	0	10	-40 - +150°C	50	10	210
1120006	60		0.4	0	8	-40 - +150°C	60	10	250
1120008	70		0.3	0	8	-40 - +150°C	70	10	290
1120009	75		0.2	0	7	-40 - +150°C	75	10	310
1120010	80		0.2	0	6	-40 - +150°C	80	10	330
1120012	100		0.2	0	5	-40 - +150°C	100	10	560
1120013	110		0.2	0	5	-40 - +150°C	110	10	600
1120014	115		0.2	0	4	-40 - +150°C	115	10	630
1120015	120		0.2	0	4	-40 - +150°C	120	10	670
1120016	125		0.1	0	4	-40 - +150°C	125	10	700
1120017	130		0.1	0	4	-40 - +150°C	130	10	720
1120018	140		0.1	0	4	-40 - +150°C	140	10	730
1120019	150		0.1	0	4	-40 - +150°C	150	10	780
1120020	160		0.1	0	3	-40 - +150°C	160	10	800
1120025	175		0.1	0	3	-40 - +150°C	175	10	820
1120024	180		0.1	0	2	-40 - +150°C	180	10	850
1120021	200		0.1	0	2	-40 - +150°C	200	10	1270
1120022	250		0.1	0	2	-40 - +150°C	250	10	1600
1120023	300		0.1	0	1	-40 - +150°C	300	10	1450
1120027	350		0	0	1	-40 - +150°C	350	10	1550
1120028	400		0	0	1	-40 - +150°C	400	10	2000