

**GEM S**
**Furtun din silicon**


Furtun cu tubul de silicon , potrivit pentru o varietate de aplicatii (fara presiune) unde rezistenta chimica si de temperatura sunt necesare.

Indeplineste norma: FDA 21 CFR 177.2600.

Alte culori si diametre disponibile la cerere.

Exterior: Silicon  
 Interior: Silicon  
 Culoare exterior: Semi transparent  
 Culoare interior: Semi transparent

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
1800003	2	4	0	0		-60 - +180°C		100	12
1800012	4	6	0	0		-60 - +180°C		100	19
1800013	4	7	0	0		-60 - +180°C		100	31
1800014	4	8	0	0		-60 - +180°C		25	45
1800019	5	8	0	0		-60 - +180°C		50	36
1800023	6	9	0	0		-60 - +180°C		100	42
1800024	6	10	0	0		-60 - +180°C		50	59
1800026	6	12	0	0		-60 - +180°C		25	101
1800027	7	9	0	0		-60 - +180°C		100	30
1800032	8	10	0	0		-60 - +180°C		100	34
1800034	8	12	0	0		-60 - +180°C		50	74
1800039	9	12	0	0		-60 - +180°C		50	58
1800043	10	12	0	0		-60 - +180°C		50	41
1800044	10	14	0	0		-60 - +180°C		50	89
1800046	10	16	0	0		-60 - +180°C		25	145
1800047	12	14	0	0		-60 - +180°C		25	48
1800048	12	16	0	0		-60 - +180°C		50	104
1800075	25	30	0	0		-60 - +180°C		25	245
1800077	25	33	0	0		-60 - +180°C		25	430
1800078	30	40	0	0		-60 - +180°C		25	648
1800115	38	48	0	0		-60 - +180°C		20	797