

POLARIS
Furtun PTFE (Teflon) striat cu tresa de Otel Inox


Furtun utilizat pentru aplicatii de inalta calitate in industria alimentara, cosmetica, farmaceutica si industriii biologice. Tresa din otel inox la exterior pentru protectie furtun.

Exterior:	Otel Inox , AISI 304
Interior:	PTFE
Culoare exterior:	Argintiu
Culoare interior:	Alb
Exterior electroconductiv:	$R < 10^6 \Omega$
Norma:	FDA 21 CFR 177.1550 EC 1935/2004

Articol Nr.	Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
550018	6	9.9	172	517	80	-70 - +260°C	18	100	140
550019	8	12.9	138	414	80	-70 - +260°C	20	100	160
550004	10	14.5	138	414	80	-70 - +260°C	20	100	152
550001	13	19.2	103	310	80	-70 - +260°C	25	100	253
550021	16	24	83	248	80	-70 - +260°C	51	100	304
550002	19	27	69	207	80	-70 - +260°C	64	100	374
550003	25	36.1	46	138	80	-70 - +260°C	89	100	543
550022	32	41.3	34	103	80	-70 - +260°C	125	100	635
550014	38	49	30	90	80	-70 - +260°C	152	100	840
550023	50	62.3	23	69	80	-70 - +260°C	200	100	1000