

Applications: Machine ideal for small sites or restructuring work. Very quiet but also suitable for professional use.

Use: Compared to manual mixers or drills, the RAY 60 mixer does not require an operator, thus reducing the problem of transmitting vibrations and noise.



CHARACTERISTICS

- Electric safety limit switch which blocks blade rotation when the mixing group is raised
 - 2 plastic drums supplied as standard
 - Grip handle for manoeuvring
- Machine supplied dismantled in box packing

CHARACTERISTICS 60

- Single phase motor 230V/50 Hz
- Switch with IP 55 minimum voltage coil and plug
- Universal mixing blade
- Motor reducer with gear reducer in oil-bath



TECHNICAL DATA

| | | 60 | 120 | 240 |
|-----------------------------------|-----|---------------|---------------|----------------|
| Drum capacity | lt | 56 | 130 | 220 |
| Effective output | Lt. | 47 | 70 | 150 |
| Drum diameter | Cm | 1350 | | |
| N° blade revs | Rpm | 55 | | |
| Machine weight | Kg. | 30 | 110 | 177 |
| Wheel dimensions | mm | 100 x 20 | 250 x 25 | 250 x 25 |
| Single phase electric motor power | Kw | 0,55 | 0,75 | 1,85 |
| Absorption | A | 5 | 5 | 5 |
| Lpa g Value | dB | 77 | 72 (LW) | 95 (lw) |
| Machine dimensions L x W x H | Cm | 104 / 80 / 58 | 88 / 88 / 100 | 101 / 92 / 106 |
| Package dimensions L x W x H | Cm | 62 / 46 / 58 | | |