Vertical balers

X-series X25 AD



ERGONOMICAL BALING

The X25 AD is equipped with cross cylinders, giving you stable compression and superior press force, together with a low overall height. Combined with a long stroke, a high bale weight can be achieved.

The X25 AD has an unique sliding door that closes and opens fully automatically. This gives the operator an ergonomical and quick filling of waste, still complying with the highest level of safety.







1 Compact your waste and eject the finished bale. **2** Remove and store the bale until collection. **3** The cross cylinders ensure stable compression and a low overall height. **4** The bale is ejected by a safe two-hand operation.

Noiseless

Due to an unique hydraulic system

- Safe and steady opening of door Operated by a strong threaded spindle
- Easy installation
- Very low overall height

Schuster SRL Str. Al. Vlahuta, Nr 11 Bihor, 410086 Oradea Tel. +40 359 467 066 Fax +40 359 461 961 office@schuster-teh.ro www.schuster-teh.ro



Technical specifications	
Press force (t)	25
Power supply	3x230/400V 50Hz 25/16A
Motor (kW)	4.0
Noise level (dB)	59-60
Cycle time (sec)	23
Dimensions WxDxH (mm)	1745 x 1390 x 1995
Weight (kg)	1425
Filling opening WxH (mm)	1090 x 530
Filling height (mm)	940
Chamber height (mm)	1380
Stroke (mm)	950
Bale size WxDxH (mm)	1200 x 800 x 800
Bale weight cardboard (kg)	250-300
Bale weight plastic (kg)	300-400

