

# Hyper L

GUARANTEED

## Hyper L (three phase)


Panel with analogic controls

Easy access to main mechanical components

Heavy frame



BL4 21-200



**Standard equipment:**

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m



• Main pump components are interchangeable with some other pump manufacturer.



• 4 poles (1450rpm) electric motor with: water cooling



• Integrated elastic joint, for best pump coupling.

**Optional:**

- Hose-reel with brake (hose not included) cod.3.697.0044



**HYPER L 1515 LP**

**HYPER L 2015 LP**

|                              |                           |                           |
|------------------------------|---------------------------|---------------------------|
| Code                         | 8.621.0907                | 8.621.0908                |
| operat. pressure/max         | 30÷150 bar                | 30÷200 bar                |
| operat. pressure/max         | 435÷2175 psi              | 435÷2900 psi              |
| delivery rate                | 330÷660 l/h               | 450÷900 l/h               |
| delivery rate                | 1.52÷2.91 GPM             | 1.98÷3.96 GPM             |
| abs. power/voltage           | 5500W-400V-50Hz           | 7300W-400V-50Hz           |
| RPM                          | 1450                      | 1450                      |
| diesel tank/detergent tank   | 18/3,0 l.-4.8/0.79 gal    | 18/3,0 l.-4.8/0.79 gal    |
| max temp. inlet/outlet       | 40 °C / 140 °C            | 40 °C / 140 °C            |
| fuel consumption/heat output | 3,78 l/h -1 gal/h / 42 kW | 3,78 l/h -1 gal/h / 42 kW |
| machine dimensions           | 94x65x90 cm               | 94x65x90 cm               |
| machine weight               | 133 kg / 292.6 lbs        | 135 kg / 297 lbs          |