

Syntetic Media Rolls



Advantages

- Progressively built up thermal bonded polyester fibre

Application: For use as a pre filter in air conditioning, and spraybooth ventilation.

Flammability: (DIN 53438) self extinguishing.

Media: Synthetic.

EN779:2012 efficiency: G2, G3, G4.

Arrestance efficiency: 65% - 92%.

Eurovent 4/5 efficiency: EU2, EU3, EU4.

Temperature: 80°C - 100°C maximum in continuous service.

Humidity: 100% RH.

Model	Dimensions (metres)	Filter classification EN779:2012	Media area m ²	Velocity / pressure drop m/s/Pa	Unit volume m ³	Dust holding g/m ²	Pack qty
T15-150	2.05 x 20	G2	41	1.5 / 15	0.53	410	1
T15-150	1.0 x 20	G2	20	1.5 / 15	0.26	410	1
PST 290	2.05 x 20	G4	41	1.10 / 41	0.82	350	1
PST 290	1.0 x 20	G4	20	1.10 / 41	0.40	350	1
PST 290	0.76 x 20	G4	15	1.10 / 41	0.30	350	1
T15-350	2.05 x 20	G4	41	1.5 / 25	0.62	678	1
T15-500	2.05 x 20	G4	41	1.5 / 35	0.08	540	1
POLY 50	2.05 x 20	G3	41	1.5 / 45	2.05	550	1
POLY SOFT 50	2.0 x 10	G3	20	1.5 / 52	1.00	673	1
POLY SOFT 50	2.0 x 20	G3	40	1.5 / 52	2.00	673	1
HC - 80	1.0 x 50	G2	50	1.5 / 12	0.50	360	1

Other sizes and cut pads available on request.