

EKO –CK		14	20	25	30	35	40
Puterea termica	(kW)	14	15-20	20-25	25-30	30-35	35-40
Continut de apa	(l)	59	60	64	67	76	78
Greutate cazan	(kg)	220	227	234	255	266	293
Diam./inalt. rac. cos	(mm)	150/930	150/930	150/930	160/930	160/930	180/930
Deschid. usa sup. (lxl)	(mm)	321x273	321x273	321x273	371x273	421x273	471x273
Deschid. usa inf. (lxl)	(mm)	321x322	321x322	321x322	371x322	421x322	471x322
Tiraj cos	(Pa)	15	16	18	19	20	21
Racord tur/retur	(R")	5/4	5/4	5/4	5/4	5/4	5/4
Rac. umplere /golire	(R")	1/2	1/2	1/2	1/2	1/2	1/2
T. gaze arse (m/g)	(°C)	170	170	170	170	170	170
T. gaze arse (lemn)	(°C)	190	190	190	190	190	190
Temp. max. de lucru	(°C)	90	90	90	90	90	90
Pres. max. de lucru	(bar)	2,5	2,5	2,5	2,5	2,5	2,5
Adancime cazan	(mm)	985	985	1020	1020	1020	1020
Inaltime cazan	(mm)	1255	1255	1255	1255	1255	1255
Latime corp cazan	(mm)	420	420	420	420	520	570
Latime totala cazan	(mm)	470	470	470	470	570	620
Adanci. baza cazan	(mm)	565	565	600	600	600	600
Inaltime racord retur	(mm)	485	485	485	485	485	485
Lungime max. lemne	(mm)	500	500	500	500	500	500

EKO –CK		50	60	70	90	110
Puterea termica	(kW)	40-50	50-60	50-70	70-90	90-110
Continut de apa	(l)	96	118			
Greutate cazan	(kg)	337	355			
Diam./inalt. rac. cos	(mm)	180/1025	180/1025	200/1085	200/1085	200/1085
Deschid. usa sup. (lxl)	(mm)	471x273	471x273	471x275	521x275	521x275
Deschid. usa inf. (lxl)	(mm)	471x322	471x322	471x422	521x422	521x422
Tiraj cos	(Pa)	23	25	26	29	31
Racord tur/retur	(R")	5/4	5/4	6/4	2	2
Rac. umplere /golire	(R")	1/2	1/2	1	1	1
T. gaze arse (m/g)	(°C)	180	180	190	200	200
T. gaze arse (lemn)	(°C)	220	220	230	240	240
Temp. max. de lucru	(°C)	90	90	90	90	90
Pres. max. de lucru	(bar)	2,5	2,5	2,5	2,5	2,5
Adancime cazan	(mm)	1142	1142	1250	1250	1350
Inaltime cazan	(mm)	1255	1355	1430	1430	1430
Latime corp cazan	(mm)	570	570	570	620	620
Latime totala cazan	(mm)	620	620	640	690	690
Adanci. baza cazan	(mm)	725	725	815	815	915
Inaltime racord retur	(mm)	485	485	630	630	630
Lungime max. lemne	(mm)	600	600	650	650	700