

| Bio-Tec | | 25 | 35 | 45 |
|------------------------------|-------|-----------|-----------|-----------|
| Puterea termica | (kW) | 25 | 35 | 45 |
| Continut de apa in cazan | (lit) | 105 | 96 | 110 |
| Greutate cazan | (kg) | 450 | 515 | 610 |
| Racord gaze arse (ext.) | (mm) | 150 | 150 | 180 |
| Racord tur/retur cazan | (R") | 6/4 | 6/4 | 6/4 |
| Rac. umplere /golire | (R") | 1/2 | 1/2 | 1/2 |
| Temp. gaze arse (lemn) | (°C) | 170 | 190 | 180 |
| Temp. max. de lucru | (°C) | 90 | 90 | 90 |
| Pres. max. de lucru | (bar) | 2,5 | 2,5 | 2,5 |
| Adancime totala cazan | (mm) | 1295 | 1290 | 1290 |
| Inaltime totala cazan | (mm) | 1345 | 1385 | 1580 |
| Latime totala cazan | (mm) | 595 | 725 | 725 |
| Dim. baza cazan - Lat. X Ad. | (mm) | 430 x 685 | 540 x 685 | 540 x 885 |
| Inaltime racord tur | (mm) | 1285 | 1330 | 1525 |
| Inaltime racord retur | (mm) | 80 | 80 | 80 |
| Inaltime racord gaze arse | (mm) | 765 | 1040 | 1250 |
| Lungime max. lemne | (mm) | 550 | 550 | 550 |
| Volum incarcare lemne | (lit) | 97 | 132 | 195 |