

ALUMINIU

Formate si grosimi standard

INFORMATIV

M R G Stainless Group S.R.L.
Bulevardul 1Mai nr. 32 Bucuresti
Telefon +40 31-410 48 12 * Fax +40 31-410 48 12
Mobil +40 72-134 40 99
e-mail: mrgstainlessgroup@yahoo.com
www.mrgstainlessgroup.home.ro
www.aluminiu-cupru-inox.home.ro

Bare dreptunghiulare, trase, lungimea STAS 3000 mm
(EN 573-3, EN 754)

AISI 1 MgMn - EN AW 6082

Cod	Dimens. (mm)	Stare	kg/ml
	30 x 15	T 6	1,250
	32 x 16	T 6	1,440
	40 x 15	T 6	1,700
	40 x 20	T 6	2,240
	40 x 30	T 6	3,380
	55 x 25	T 6	3,900
	52 x 26	T 6	3,800
	75 x 71	T 6	14,500

Bare dreptunghiulare, extrudate, lungimea STAS 3000 mm
(EN 573-3, 755)

AlMgSiPb - EN AW 6012

Cod	Dimens. (mm)	Stare	kg/ml
	83 x 78	T 6	18,400

Bare dreptunghiulare, trase, pt. automate, lungimea STAS 3000 mm
(DIN 1747 / 1769, EN 573-3, 754)

AlMgSiPb - EN AW 6012

Cod	Dimens. (mm)	Stare	kg/ml
	40 x 16	T 6	1,840
	70 x 45	T 6	9,130
	77 x 40	T 6	8,600
	80 x 40	T 6	9,130
	89 x 40	T 6	9,950

Bare dreptunghiulare, trase, pt. automate, lungimea STAS 3000 mm
(DIN 1747 / 1769, EN 573-3, 754)

AlCu 4 PbMgMn - EN AW 2007

Cod	Dimens. (mm)	Stare	kg/ml
	20 x 12	T 351	0,630
	20 x 15	T 351 PQ	0,840
	22 x 16	T 351 PQ+abatere	1,000
	25 x 10	T 351	0,700
	25 x 20	T 351	1,410
	30 x 16	T 351 PQ	1,440
	30 x 20	T 351 PQ+abatere	1,750
	32 x 15	T 351 PQ	1,390
	32 x 22	T 351 PQ	2,050
	36 x 18	T 351 PQ+abatere	1,970
	36 x 22	T 351 PQ+abatere	2,360
	40 x 20	T 351 PQ	2,340
	40 x 22	T 351 PQ+abatere	2,550
	50 x 20	T 351 PQ+abatere	2,930
	50 x 25	T 351 PQ+abatere	3,700
	50 x 30	T 351 PQ+abatere	4,390
	60 x 30	T 351 PQ+abatere	5,260
	60 x 40	T 351	6,940
	62 x 55	T 351 PQ	9,790
	70 x 25	T 351 PQ+abatere	5,100
	70 x 45	T 351 PQ	9,130
	80 x 25	T 351 PQ	5,900

Bare dreptunghiulare, extrudate, lungimea STAS 3000 mm
(EN 573-3, 755)

AlCu 4 PbMgMn - EN AW 2007

Cod	Dimens. (mm)	Stare	kg/ml
	20 x 10	T 4	0,600
	25 x 10	T 4	0,700
	25 x 15	T 4	1,020
	30 x 10	T 4	0,850
	30 x 15	T 4	1,200
	30 x 20	T 4	1,700
	40 x 10	T 4	1,200
	40 x 15	T 4	1,760
	40 x 20	T 4	2,340
	40 x 30	T 4	3,510
	45 x 30	T 4	4,000
	50 x 10	T 4	1,470
	50 x 15	T 4	2,200
	50 x 20	T 4	2,930
	50 x 30	T 4	4,390
	50 x 40	T 4	5,800
	55 x 40	T 4	6,360
	60 x 15	T 4	2,510
	60 x 20	T 4	3,510
	60 x 30	T 4	5,260
	60 x 40	T 4	7,020
	80 x 15	T 4	3,350
	80 x 20	T 4	4,680
	80 x 30	T 4	6,700
	80 x 35	T 4	8,560
	80 x 40	T 4	9,350
	80 x 50	T 4	11,690
	90 x 30	T 4	7,950
	100 x 10	T 4	2,930
	100 x 20	T 4	5,850
	100 x 40	T 4	11,590
	100 x 50	T 4	14,610
	120 x 50	T 4	19,700
	120 x 60	T 4	20,910
	150 x 50	T 4	21,630

Bare dreptunghiulare, extrudate, (pt. MATRITE), lungimea STAS 3000 mm
(EN 573-3, 755)

AlZn5.5MgCu - EN AW 7075

Cod	Dimens. (mm)	Stare	kg/ml
	50 x 300	T 6510	42,840
	80 x 150	T 6510	34,270
	80 x 250	T 6510	57,120
	100 x 150	T 6510	42,840
	120 x 200	T 6510	68,540

Bare patrate, extrudate, lungimea STAS 3000 mm
(DIN 1747 / 59700, EN 573-3, 755)

AISI 1 MgMn - EN AW 6082

Cod	Dimens. (mm)	Stare	kg/ml
	10 x 10	T 6	0,300
	15 x 15 x 3250	T 6	0,700
	20 x 20	T 6	1,120
	25 x 25	T 6	1,800
	30 x 30	T 6	2,550
	35 x 35	T 6	3,640
	40 x 40	T 6	4,550
	50 x 50	T 6	6,970
	55 x 55	T 6	8,720
	60 x 60	T 6	10,200
	70 x 70	T 6	13,850
	80 x 80	T 6	17,850
	90 x 90	T 6	22,760
	100 x 100	T 6	28,000
	110 x 110	T 6	32,950
	120 x 120	T 6	42,130
	130 x 130	T 6	46,740
	150 x 150	T 6	67,810

Bare patrate, trase, lungimea STAS 3000 mm
(EN 573-3, 754)

AISI 1 MgMn - EN AW 6082

Cod	Dimens. (mm)	Stare	kg/ml
	30 x 30	T 6	2,570
	40 x 40	T 6	4,500
	46 x 46	T 6	5,950
	50 x 50	T 6	6,970
	80 x 80	T 6	17,850

Bare patrate, trase, pt. automate, lungimea STAS 3000 mm
trase (EN 573-3, 754); extrudate (EN 755)

AlCu 4 PbMgMn - EN AW 2007

Cod	Dimens. (mm)	Stare	kg/ml
	22 x 22	T 351 PQ	1,440
	25 x 25	T 351	1,830
	30 x 30	T 351 PQ	2,670
	35 x 35	T 351 PQ	3,590
	40 x 40	T 351 PQ	4,620
	50 x 50	T 351 PQ	7,330
	55 x 55	T 351 PQ	8,500
	60 x 60	T 351 PQ	10,520
	65 x 65	T 351	12,200
	66 x 66	T 351 PQ	12,610

Bare patrate, extrudate, lungimea (L - 3000 mm)
(EN 755)

AlCu 4 PbMgMn - EN AW 2007

Cod	Dimens. (mm)	Stare	kg/ml
	15 x 15	T 4	0,630
	20 x 20	T 4	1,170
	25 x 25	T 4	1,850
	40 x 40	T 4	4,700
	50 x 50	T 4	7,310
	70 x 70	T 4	14,150
	80 x 80	T 4	18,700
	90 x 90	T 4	23,670
	100 x 100	T 4	29,220
	120 x 120	T 4	42,500

Bare patrate, extrudate, pt. automate, lungimea STAS 3000 mm (EN 573-3, 755)			AlMgSiPb - EN AW 6012
Cod	Dimens. (mm)	Stare	kg/ml
	50 x 50	T 6	7,540
	70 x 70	T 6	13,840
	80 x 80	T 6	17,790
	90 x 90	T 6	22,550

Bare patrate pt automate, trase (L - 3000 mm) (EN 573-3, 754)			AlCuMgSn - AA 2015
Cod	Dimens. (mm)	Stare	kg/ml
	25 x 25	T 351	1,890
	30 x 30	T 351	2,660
	50 x 50 (rotunjit)	T 351	7,100

Bare rotunde, trase, lungimea STAS 3000 mm (DIN 1747 / 1798, EN 573-3, 754)			AISI 1 MgMn - EN AW 6082
Cod	Dimens. (mm)	Stare	kg/ml
	5	T 6	0,100
	8	T 6	0,150
	10	T 6	0,230
	12	T 6	0,330
	14	T 6	0,450
	15	T 6	0,510
	16	T 6	0,640
	18	T 6	0,750
	20	T 6	0,870
	22	T 6	1,100
	24	T 6	1,360
	25	T 6	1,370
	26	T 6	1,560
	28	T 6	1,850
	30	T 6	2,000
	32	T 6	2,330
	35	T 6	2,700
	40	T 6	3,600
	63	T 6	8,860

Bare rotunde, extrudate, lungimea STAS 3000 mm (DIN 1747 / 1799, EN 573-3, 755)			AISI 1 MgMn - EN AW 6082
Cod	Dimens. (mm)	Stare	kg/ml
	8 (AlMgSi0.5 - moale)	T 6	0,150
	15	T 6	0,510
	18	T 6	0,800
	20	T 6	0,900
	25	T 6	1,410
	30	T 6	2,000
	32	T 6	2,260
	35	T 6	2,770
	40	T 6	3,600
	42	T 6	3,950
	44	T 6	4,260
	45	T 6	4,410
	50	T 6	5,500
	55	T 6	6,580
	56	T 6	7,000
	60	T 6	7,900
	65	T 6	9,350
	70	T 6	10,650

	75	T 6	12,230
	80	T 6	13,900
	83	T 6	15,380
	85	T 6	16,610
	90	T 6	18,380
	95	T 6	20,620
	100	T 6	21,770
	110	T 6	26,000
	120	T 6	32,680
	125	T 6	34,030
	130	T 6	38,750
	140	T 6	42,950
	150	T 6	48,800
	160	T 6	59,350
	170	T 6	63,550
	180	T 6	71,250
	190	T 6	79,030
	200	T 6	86,920
	210	T 6	104,400
	220	T 6	109,170
	240	T 6	123,500
	250	T 6	135,300
	280	T 6	174,250
	300	T 6	195,780
	350	T 6	268,550

Bare rotunde pt. automate, anodizabile, lungimea STAS 3000 mm
trase (EN 573-3, 754); extrudate (EN 755)

AlMgSiPb - EN AW 6012

Cod	Dimens. (mm)	Stare	kg/ml
	12	T 6	0,330
	14	T 6	0,450
	15	T 6	0,540
	16	T 6	0,570
	18	T 6	0,750
	20	T 6	0,950
	22	T 6	1,100
	25	T 6	1,400
	26	T 6	1,540
	28	T 6	1,850
	30	T 6	2,160
	32	T 6	2,260
	33	T 6	2,420
	35	T 6	2,710
	36	T 6	3,070
	40	T 6	3,800
	42	T 6	3,910
	43	T 6	4,470
	45	T 6	4,510
	48	T 6	5,130
	50	T 6	5,800
	51	T 6	5,950
	55	T 6	6,880
	56	T 6	7,430
	60	T 6	8,170
	65	T 6	9,430
	80	T 6	14,250
	100	T 6	23,120
	110	T 6	26,650
	120	T 6	32,900
	150	T 6	50,230

Bare rotunde cu rezistență ridicată, trase, lungimea STAS 3000 mm
trase (EN 573-3, 754); extrudate (EN 755)

AlZn 5.5 Mg Cu - EN AW 7075


Cod	Dimens. (mm)	Stare	kg/ml
	9	T 651	0,200
	12	T 651	0,340
	20	T 651	0,910
	22	T 651	1,210
	25	T 651	1,410
	30 (EN 755 extrudate)	T 651	2,140
	40	T 651	3,610
	45 (EN 755 extrudate)	T 651	4,570
	50	T 651	5,700
	55	T 651	6,850
	60	T 651	8,120
	70	T 651	11,050
	80	T 651	14,430
	90	T 651	18,250
	100	T 6	22,580
	110	T 6510	27,270
	120	T 6	32,500
	130	T 6	38,080
	140	T 6	44,180
	150	T 6	51,100
	160	T 6	58,800
	170	T 6	64,000
	180	T 6	72,990
	200	T 6	91,260
	220	T 6	113,270
	250	T 6	141,450
	300	T 6	205,000
	350	T 6	278,800

Bare rotunde, trase, pt. automate, lungimea STAS 3000 mm
(DIN 1747 / 1798, EN 573-3, 754)


AlCu 4 PbMgMn - EN AW 2007

Cod	Dimens. (mm)	Stare	kg/ml
	6	T 351	0,080
	8	T 351	0,150
	10	T 351	0,230
	11	T 351	0,270
	12	T 351	0,340
	13	T 351	0,390
	14	T 351	0,450
	15	T 351	0,520
	16	T 351	0,620
	18	T 351	0,810
	19	T 351	0,830
	20	T 351	0,910
	22	T 351	1,150
	23	T 351	1,210
	24	T 351	1,420
	25	T 351	1,500
	26	T 351	1,690
	27	T 351	1,750
	28	T 351	1,800
	30	T 351	2,100
	32	T 351	2,460
	35	T 351	2,800
	36	T 351	2,980
	38	T 351	3,390
	38,5	T 351	3,420
	40	T 351	3,630
	42	T 351	4,000


	42,2	T 351	4,110
	44	T 351	4,430
	45	T 351	4,550
	48	T 351	5,050
	50	T 351	5,680
	50,6	T 351	5,900
	52	T 351	6,210
	55	T 351	6,870
	56	T 351	7,430
	60	T 351	8,200

Bare rotunde, extrudate, pt. automate, lungimea STAS 3000 mm AlCu 4 PbMgMn - EN AW 2007
(DIN 1747 / 1799, EN 573-3, 755) 


Cod	Dimens. (mm)	Stare	kg/ml
	20	T 4510	0,930
	25	T 4510	1,440
	30	T 4510	2,210
	32	T 4510	2,360
	35	T 4510	2,870
	40	T 4510	3,630
	45	T 4510	4,600
	50	T 4510	5,700
	55	T 4510	6,870
	56	T 4510	7,440
	60	T 4510	8,200
	63	T 4510	9,020
	65	T 4510	9,590
	70	T 4510	10,990
	71	T 4510	11,480
	72	T 4510	11,700
	75	T 4510	12,900
	80	T 4511	14,680
	85	T 4	16,200
	90	T 4	18,580
	100	T 4	22,690
	105	T 4	25,900
	110	T 4	27,460
	120	T 4	32,680
	125	T 4	33,970
	130	T 4	38,800
	140	T 4	44,950
	150	T 4	51,600
	160	T 4	58,710
	170	T 4	65,600
	180	T 4	73,240
	200	T 4	92,720
	210	T 4	103,100

Bare rotunde, trase, pt. automate, lungimea STAS 3000 mm AlCu 4 Mg 1 - EN AW 2024
(DIN 1747 / 1798, EN 573-3, 754) 


Cod	Dimens. (mm)	Stare	kg/ml
	25	T 3	1,400

Bare rotunde, trase, pt. automate, lungimea STAS 3000 mm AlCu 6Bi Pb - EN AW 2011
(DIN 1747 / 1798, EN 573-3, 754) 


Cod	Dimens. (mm)	Stare	kg/ml
	48	T 3	5,600
	58	T 3	7,400

Bare rotunde eloxabile trase, pt. automate, ecologice, lungimea STAS 3 m AlMgSiSnBi - AA 6023
 (DIN 1747 / 1798, EN 573-3, 754) fara plumb 


Cod	Dimens. (mm)	Stare	kg/ml
	15	T 9	0,550
	18	T 9	0,820
	20	T 9	0,930
	22	T 9	1,130
	25	T 9	1,440
	26	T 9	1,560
	28	T 9	1,850
	30	T 9	2,160
	33	T 6	2,600
	36	T 9	2,980
	36,5	T 9	3,030
	40	T 9	3,690
	50	T 6	5,800
	50	T 9	5,800
	51	T 6	5,950
	55	T 6	6,920

Bare rotunde eloxabile trase, pt. automate, ecologice, lung. STAS 3000 mm AlCuSnBi - AA 2111 B
 (DIN 1747 / 1798, EN 573-3, 754) fara plumb 


Cod	Dimens. (mm)	Stare	kg/ml
	20	T 6	0,930
	60	T 6	8,310

Bare rotunde eloxabile extrudate, pt. automate, ecologice, STAS 3000 mm AlMgSiSnBi - AA 6023
 (DIN 1747 / 1798, EN 573-3, 755) fara plumb 

Cod	Dimens. (mm)	Stare	kg/ml
	51	T 6	5,950
	53	T 6	6,350
	100	T 6	23,000
	120	T 6	31,300

Bare rotunde eloxabile trase, pt. automate, ecologice, L. STAS 3000 mm AlCuMgSn - AA 2015
 (DIN 1747 / 1798, EN 573-3, 754) fara plumb 

Cod	Dimens. (mm)	Stare	kg/ml
	18	T 351	0,820
	20	T 351	0,930
	22	T 351	1,130
	25	T 3	1,400
	26	T 3	1,520
	30	T 351	2,160
	32	T 3	2,360
	45	T 3	4,100
	50	T 351	5,800

Bare rotunde eloxabile extrudate, pt. automate, ecologice, STAS 3000 mm AlCuMgSn - AA 2015
 (DIN 1747 / 1798, EN 573-3, 755) fara plumb 

Cod	Dimens. (mm)	Stare	kg/ml
	50	T 4511	5,800
	70	T 4511	11,130
	100	T 4511	23,120