

SPECIFICATIONS/SECTIONS

Univer REI 60 double-leaf doors



Univer REI 60 double-leaf doors:

- ❑ **Galvanized** steel-sheet reversible door leaf with insulating-material core, total thickness 50 mm.
- ❑ Corner reversible frame, with or without bottom frame, made of **galvanized** steel-sheet profile, including preparation for plugs. The frame is supplied non-assembled.
- ❑ Reversible opening pull right (DX), transformable in pull left (SX) for standard, semistandard and to order door version.
- ❑ Full lock in main leaf with cylinder bore and plastic keyhole for patent key, included.
- ❑ Self-locking mechanism with built-in release lever on secondary door leaf.
- ❑ Milled slot for the automatic blocking lock on the secondary door leaf prepared for the application of panic hardware.
- ❑ Safety bolt in hinge-side leaf edge.
- ❑ Black safety handle with steel core, supplied with plates, cylinder bore and keyholes for patent keys.
- ❑ 4 hinges, one per leaf with spring for the self-closing and one per leaf ball-bearing with screws for the vertical adjustment.
- ❑ Locking regulator to guarantee the correct locking sequence.
- ❑ Strengthening plates inside door leaf for fastening door closer and emergency handle if required.
- ❑ Floor catch to be fitted by means of screws/plugs onto the finished floor.
- ❑ Thermoexpanding gasket inserted in appropriate cavity in frame.
- ❑ Identification plate on door edge.
- ❑ Standard epoxy-polyester oven-baked powder coated with anti-scratch beaten finish - light pastel turquoise for door leaves (NCS4020-B50G), and a darker shade for the frame (NCS5020-B50G). By request, powder coating in RAL or decorative NDD - Ninz Digital Decor can be applied for decorative or graphic elements. Surface treatment of the door leaves is carried out using oven-baked epoxy-polyester powder and graphic printing of the decoration on the flat side of the door leaves by means of sprayed inks. The decoration is protected by transparent varnish. The finishing can be smooth or embossed in accordance with the decoration selected.
- ❑ Maximum dimensions: 2000 x 2150 mm.
- ❑ Weight approx. 33 kg/m² wall opening.

N.B.

- Cylinder and weather stripping are supplied only upon request.
- All the RAL colours available are listed on the order form and on the page on "surface finishing".
- For door repainting follow instructions on page "surface treatment".
- FFL = Finished floor level.

