



Dimensioni in mm

MODELLI	A	B	C	D	E	F	G	H	I	L	M	N
MFI 400 P	2200	1805	970	1155	170	490	495	785	2780	2500	2205	2375
MFI 600 P	2200	1805	1170	1410	225	590	595	785	2780	2500	2205	2375
MFI 800 P	2200	1805	1370	1710	225	725	760	785	2780	2500	2205	2375
MFI 1200 P	2200	1805	1870	2165	280	925	960	785	2780	2500	2205	2375
MFI/RV 400	2200	1805	970	1155	170	490	495	785	2780	2500	2205	2375
MFI/RV 600	2200	1805	1170	1410	225	590	595	785	2780	2500	2205	2375
MFI/RV 800	2200	1805	1370	1610	225	690	695	785	2780	2500	2205	2375
MFI/RV 1200	2200	1805	1870	2165	280	925	960	785	2780	2500	2205	2375

Caratteristiche tecniche

MODELLI	Pezzatura alimentazione mm	Alimentazione ton/h	Potenza motori kW	Resa in vagliatura con rete luce foro 5 mm	Resa in vagliatura con rete luce foro 10÷12 mm	Giri rotore N°/1'	Peso kg
MFI 400 P	8÷80	25÷35	30÷75	55÷65%	80÷90%	725÷825	7000
MFI 600 P	8÷80	30÷60	55÷110	55÷65%	80÷90%	725÷825	7600
MFI 800 P	8÷80	40÷90	75÷160	55÷65%	80÷90%	725÷825	10.100
MFI 1200 P	8÷80	70÷150	132÷200	55÷65%	80÷90%	725÷825	12.100
MFI/RV 400	6÷30	20÷32	30÷75	80÷90%	95%	950÷1055	6000
MFI/RV 600	6÷30	30÷50	55÷110	80÷90%	95%	950÷1055	7250
MFI/RV 800	6÷30	30÷80	110÷132	80÷90%	95%	950÷1055	8850
MFI/RV 1200	6÷30	70÷150	132÷200	80÷90%	95%	950÷1055	10400