



MODELLI	Dimensioni in mm												
	A	B	C	D	E	F	G	H	I	L	M	N	
MS 4/6	608	660	738	658	625	1508	2245	2410	1550	1025	1120	2365	
MS 4/8	808	660	938	758	725	1708	2245	2410	1550	1025	1120	2365	
MS 6/10	1008	800	1148	932	888	2100	2385	2825	1925	1070	1225	2500	
MS 6/12	1208	800	1348	1000	965	2245	2385	2825	1925	1070	1225	2500	
MS 8/14	1408	800	1548	1090	1070	2440	2500	3000	1950	1150	1350	2650	
MS 8/16	1608	750	1770	1270	1210	2760	2890	3500	2180	1350	1470	2990	

Caratteristiche tecniche

MODELLI	Alimentazione ton/h	Pezatura alimentazione mm	Potenza kW	Dimensioni bocca mm	Giri rotore N°/1'	Peso kg	Martelli	
							N°	cad. kg
MS 4/6	35÷70	50÷150/200	55÷90	608x400	500÷650	9000	4	165
MS 4/8	60÷120	50÷150/200	90÷160	808x400	500÷650	13500	4	220
MS 6/10	70÷220	50÷200/300	110÷200	1008x565	480÷600	20000	4	300
MS 6/12	90÷300	50÷200/300	132÷250	1208x565	450÷600	25000	4	330
MS 8/14	90÷360	50÷200/300	160÷250	1408x750	450÷600	33000	4	400
MS 8/16	120÷420	60÷250/350	315	1608x750	450÷600	44000	4	440