



Dimensioni in mm

MODELLI	A	B	C	D	E	F	G	H	I	L	M	N	O	P	Q	S
MP 6/6	608	850	738	670	625	225	1520	2605	2900	1775	1300	1170	300	2470	2905	135
MP 7/8	808	990	938	790	745	225	1760	2605	3000	1775	1300	1170	300	2470	2905	135
MP 11/10	1008	1650	1148	932	888	280	2100	2605	3495	1775	1300	1170	500	2470	3105	135
MP 11/12	1208	1650	1348	1068	988	280	2336	2605	3495	1775	1300	1170	500	2470	3105	135
MP 13/14	1408	1850	1548	1132	1088	280	2500	2865	3980	1880	1555	1310	500	2865	3365	-
MP 15/16	1608	2100	1748	1495	1205	325	3025	2865	4220	1835	1555	1310	465	2865	3330	-

Caratteristiche tecniche

MODELLI	Alimentazione ton/h	Pezzatura alimentazione mm	Potenza kW	Dimensioni bocca mm	Giri rotore N°/1'	Peso cad. kg	N°	Martelli kg
MP 6/6	35÷60	30÷350	55÷90	608x600	450÷550	14000	4	165
MP 7/8	45÷90	30÷400	75÷132	808x700	500÷650	16000	4	220
MP 11/10	60÷160	50÷600	90÷160	1008x1150	500÷650	21000	4	283
MP 11/12	100÷300	50÷750	110÷200	1208x1150	450÷600	31100	4	330
MP 13/14	100÷370	80÷900	160÷250	1408x1300	450÷550	44000	4	400
MP 15/16	120÷450	80÷1000/1200	160÷315	1608x1500	450÷550	58000	4	440