

Cuple simetrice

GEKA (GK)



DISTRIBUITOR CU 3 CAI CU FILETE BSP

DN	Dist. între gheare	Filet	Material cupla	Garnitura standard	Tip garnitura	PN
mm	mm	mm				bar / psi
15	-	G 3/4	MS	-	-	10 / 145

SUPAPE DE SENS SI FILTRE



SUPAPA DE SENS PN 16 BAR / PN 25 BAR

DN	Filet intrare	Filet iesire	Material corp	Garnitura standard	Material clapeta	PN
mm	mm	mm				bar / psi
10	G 3/8	G 3/8	MS	NBR*	Nylon	16 / 232
13	G 1/2	G 1/2			Alama	25 / 362
20	G 3/4	G 3/4				
25	G 1	G 1				
32	G 1.1/4	G 1.1/4	MS	NBR*	Nylon	10 / 145
40	G 1.1/2	G 1.1/2			Alama	18 / 261
50	G 2	G 2				
65	G 2.1/2	G 2.1/2	MS	NBR*	Nylon	8 / 116
80	G 3	G 3			Alama	12 / 174
100	G 4	G 4				

* Temperatura de lucru: -10°C (14°F) / +110°C (230°F).

Presiune de deschidere: 0.02 bar, respectiv 0.01 bar pentru cele cu clapeta din alama DN 80 si 100.



SUPAPA DE SENS EUROPA PN 25 BAR

DN	Filet intrare	Filet iesire	Material corp	Garnitura standard	Material clapeta	PN	
mm	mm	mm				bar / psi	
10	G 3/8	G 3/8	MS	NBR*	Alama	25 / 362	
13	G 1/2	G 1/2					
20	G 3/4	G 3/4					
25	G 1	G 1					
32	G 1.1/4	G 1.1/4	MS	NBR*	Alama	18 / 261	
40	G 1.1/2	G 1.1/2					
50	G 2	G 2					
65	G 2.1/2	G 2.1/2	MS	NBR*	Alama	12 / 174	
80	G 3	G 3					
100	G 4	G 4					

* Temperatura de lucru: -10°C (14°F) / +110°C (230°F).

Presiune de deschidere: 0.02 bar, respectiv 0.01 bar pentru DN 80 si 100.



FILTRU CU FILET NYLON / INOX PENTRU SUPAPE DE SENS

DN	Filet intrare	Filet iesire	Material sita	Garnitura standard	Material filet	PN
mm	mm	mm				bar / psi
Toate	G 3/8 - G 4	-	Inox	-	Nylon	-
Toate	G 3/8 - G 4	-	Inox	-	Inox	-