

## Coliere forjate



**COLIER SL CONFORM DIN 20039 A (FABRICAT DIN FONTA MALEABILA)**

DN furtun*	DN furtun*	Marime	Diam. ext. furtun	Latime	Material	PN
mm	inch		mm	mm		bar / psi
13	1/2	S 22 <sup>1</sup>	17 - 22	17	Fm	16 / 232
13	1/2	SL 29	22 - 29	18	Fm	16 / 232
19	3/4	S 34 <sup>1</sup>	25 - 32	17	Fm	16 / 232
19	3/4	SL 34	28 - 34	18	Fm	16 / 232
25	1	SL 40	32 - 40	18	Fm	16 / 232
32	1.1/4	SL 49	39 - 49	20	Fm	16 / 232
38	1.1/2	SL 60	48 - 60	24	Fm	16 / 232
50	2	SL 72 **	56 - 72	25	Fm	16 / 232
50	2	SL 76	60 - 76	25	Fm	16 / 232
63/65	2.1/2	SL 94	77 - 94	30	Fm	16 / 232
75	3	SL 400 **	89 - 101	25	Fm	16 / 232
75	3	SL 115	94 - 115	35	Fm	16 / 232
90	3.1/2	SL 525 **	113 - 127	27	Fm	16 / 232
90	3.1/2	SL 145	115 - 145	38	Fm	16 / 232
100	4	SL 550 **	127 - 140	28	Fm	16 / 232
100	4	SL 600 **	135 - 155	27	Fm	16 / 232
125	5	SL 675 **	155 - 175	30	Fm	16 / 232
150	6	SL 769 **	175 - 195	30	Fm	16 / 232
175	7	SL 875 **	210 - 225	35	Fm	16 / 232
200	8	SL 988 **	227 - 250	35	Fm	16 / 232

<sup>1</sup> Corpul colierului si talpa nu sunt separate.

\* DN-uri sunt orientative, alegerea colierelor se face dupa diametrul exterior al furtunului astfel incat acesta sa fie cuprins in intervalul indicat in coloana a patra, evitand valorile limita.

\*\* Marimile sunt fabricate in afara standardului DIN 20039 A.



**COLIER SK CU GHEARE CONFORM DIN 20039 B (FABRICAT DIN FONTA MALEABILA)**

DN furtun*	DN furtun*	Marime	Diam. ext. furtun	Latime	Material	PN
mm	inch		mm	mm		bar / psi
13	1/2	SK 29	22 - 29	18	Fm	25 / 362
19 x 2 (flat)	3/4	SK 29 FL **	-	18	Fm	25 / 362
19	3/4	SK 34	28 - 33	21	Fm	25 / 362
25 x 2 (flat)	1	SK 34 FL **	-	21	Fm	25 / 362
25	1	SK 39	35 - 42	22	Fm	25 / 362
28	1.7/64	SK 44	42 - 45	24	Fm	25 / 362
28	1.7/64	SK 47	40 - 47	24	Fm	25 / 362
35	1.3/8	SK 51	45 - 53	25	Fm	25 / 362
35	1.3/8	SK 59	48 - 60	25	Fm	25 / 362
42	1.5/8	SK 60	55 - 60	26	Fm	25 / 362
42	1.5/8	SK 68	53 - 68	26	Fm	25 / 362
50	2	SK 73	60 - 73	30	Fm	25 / 362
50	2	SK 76	58 - 76	30	Fm	25 / 362
63/65	2.1/2	SK 88	75 - 88	30	Fm	25 / 362
75	3	SK 75	86 - 102	28	Fm	25 / 362

\* DN-uri sunt orientative, alegerea colierelor se face dupa diametrul exterior al furtunului astfel incat acesta sa fie cuprins in intervalul indicat in coloana a patra, evitand valorile limita.

\*\* Marimile sunt fabricate in afara standardului DIN 20039 B.