

## Coliere forjate



COLIER LAT CONFORM EN 14420-3 / DIN 2817

DN furtun*	DN furtun*	Perete furtun	Diam. ext. furtun	Latime	Material	PN
mm	inch	mm	mm	mm		bar / psi
13	1/2	5	22 - 24	50	AL, MS, SS	25 / 362
19	3/4	4	26 - 29	50	AL, SS	25 / 362
		6	30 - 33	50	AL, MS, SS	25 / 362
25	1	5	34 - 36	50	AL, SS	25 / 362
		6	36 - 39	50	AL, MS, SS	25 / 362
		8	40 - 43	50	AL, MS	25 / 362
32	1.1/4	6	43 - 46	50	AL, MS, SS	25 / 362
		8	47 - 50	50	AL, MS, SS	25 / 362
		10	50 - 53	50	MS	25 / 362
35	1.3/8	6	47 - 50	50	AL	25 / 362
38	1.1/2	6.5	50 - 52	50	AL, MS, SS	25 / 362
		8	53 - 56	50	AL, MS, SS	25 / 362
		10	57 - 60	50	AL, MS	25 / 362
40	1.1/2	7	53 - 56	50	AL, MS	25 / 362
		10	58 - 61	50	AL, MS, SS	25 / 362
45	1.3/4	7	58 - 61	50	AL	25 / 362
50	2	6	60 - 63	57	AL, SS	25 / 362
		8	64 - 67	57	AL, MS, SS	25 / 362
		10	69 - 71	57	AL, MS, SS	25 / 362
63 / 65	2.1/2	8 / 7	78 - 82	75	AL, MS, SS	25 / 362
65	2.1/2	10	84 - 87	75	AL, MS, SS	25 / 362
75	3	8	89 - 93	77	AL, MS, SS	25 / 362
		10	94 - 97	77	AL, MS	25 / 362
		12	98 - 101	77	AL	25 / 362
80	3	8	94 - 97	77	AL, MS	25 / 362
		10	99 - 102	77	AL, MS	25 / 362
100	4	8	114 - 119	120	AL, MS, SS	25 / 362
		10	118 - 122	120	AL, MS	25 / 362
		12	122 - 126	120	AL, MS	25 / 362
		14	126 - 130	120	AL, MS	25 / 362
		16	130 - 134	120	AL, MS	25 / 362
125	5	10	143 - 148	145	AL, MS	25 / 362
		13	149 - 154	145	AL	25 / 362
		15	153 - 158	145	AL	25 / 362
150	6	10	168 - 174	182	AL	25 / 362
		13	174 - 180	145	AL	25 / 362
		15	178 - 184	145	AL	25 / 362
200	8	12	222 - 229	243	AL	25 / 362
		16	230 - 239	243	AL	25 / 362

\* DN-urile sunt orientative, alegerea colierelor se face dupa diametrul exterior al furtunului astfel incat acesta sa fie cuprins in intervalul indicat in coloana a patra, evitand (daca este posibil) valorile limita.