

## Coliere forjate



COLIER LAT SERIE GREA CONFORM EN 14423 / DIN 2826

DN furtun*	DN furtun*	Perete furtun	Diam. ext. furtun	Latime	Material	PN
mm	inch	mm	mm	mm		bar / psi
13	1/2	5	22 - 24	65	MS	18 / 261
		6	24 - 26	65	MS, SS	18 / 261
		7	26 - 28	65	MS	18 / 261
19	3/4	6	30 - 33	65	MS	18 / 261
		7	32 - 34	65	MS, SS	18 / 261
25	1	6.5	37 - 39	65	MS	18 / 261
		7.5	39 - 41	65	MS, SS	18 / 261
		8.5	41 - 43	65	MS	18 / 261
32	1.1/4	6	43 - 46	77	MS	18 / 261
		8	47 - 50	77	MS, SS	18 / 261
38	1.1/2	8	53 - 56	90	MS, SS	18 / 261
50	2	9	67 - 69	100	MS, SS	18 / 261
		10	69 - 71	100	MS	18 / 261
		12	73 - 76	100	MS	18 / 261
65	2.1/2	10	84 - 87	102	MS	18 / 261
		12	88 - 91	102	MS	18 / 261
75	3	10	94 - 97	115	MS	18 / 261
		12	98 - 101	115	MS	18 / 261
		14	102 - 105	115	MS	18 / 261

\* DN-urile sunt orientative, alegerea colierelor se face dupa diametrul exterior al furtunului astfel incat acesta sa fie cuprins in intervalul indicat in coloana a patra, evitand (daca este posibil) valorile limita.

