

MAINTENANCE

Ultracoat Clean Polish is a ready-to-use product which may be diluted according to requirements. It has been specially developed for the maintenance of residential and commercial wooden floors varnished with the water-based varnishes of the Ultracoat line.

It gives the surface of floors a bright, shiny finish and also increases the protection against wear by forming a water-repellent film.

- Developed specifically for treating wooden floors coated with the water-based varnishes of the **Ultracoat** line.
- Suitable for both residential and commercial environments.
- Increases the level of protection against wear.
- High resistance to scratches caused by footsteps.
- No polishing required.

Cleaning and maintenance of floors with a low volume of traffic

Before applying the product, the surfaces to be treated must be thoroughly cleaned to remove all traces of dirt, dust, etc. Use **Ultracoat Universal Clean** for final cleaning.

Dilute 100 ml of **Ultracoat Clean Polish** with 10 litres of water and apply an even coat on the floor with a clean micro-fibre applicator or a well-wrung cloth.

Cleaning and maintenance of floors with a high volume of traffic

Before applying the product, the surfaces to be treated must be thoroughly cleaned to remove all traces of dirt, dust, etc.. Use **Ultracoat Universal Cleaner** to completely clean the surface so that a good adhesion is formed with the **Ultracoat Clean Polish**.

On floors with a high volume of traffic we recommend using undilutend **Ultracoat Clean Polish**.

CONSUMPTION

80/100 m²/litre for each coat without diluting the product. On large surfaces, we recommend using a wax-spreader machine to make application easier and to form a more durable, resistant surface.

Wait approximately 1 hour before stepping on treated surfaces. Clean tools immediately after use.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Ultracoat Clean Polish is not considered hazardous according to current standards and regulations regarding the classification of mixtures. It is however

ultracoat clean Polish





Diluting the product with clean water



Applying the diluted product to the floor with a microfibre cloth

TECHNICAL DATA (typical values)	
PRODUCT IDENTITY	
Product:	nonionic tenside
pH value: - diluted: - undiluted:	approx 9 approx 9
Dilution:	for weekly cleaning use 100 ml to 10 litres of water; on high traffic floors Ultracoat Clean Polish is used undiluted
Application:	microfibre applicator pad or cotton cloth
Substrate application temperature:	minimum +5°C
Package size:	1 litre
Consumption:	80-100 m² per litre solution
Drying time:	approx. 20-30 min.
Cleaning of tools:	water
Storage:	24 months in its original packaging
Hazard classification according to EC 1999/45:	none. Before using refer to the "Safety instructions for preparation and application" paragraph and the information on the packaging and Safety Data Sheet

recommended to use gloves, eyes protection and to take the usual precaution taken when handling chemical products are recommended.

For further and complete information about the safe use of our product please refer to our latest version of the Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject

to confirmation after long-term practical application: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our web site www.mapei.com

All relevant references for the product are available upon request and from www. mapei.com

