



02

## Distance measurement directly in machines or sites with RS-232 interface

### Features

- Digital sliding calliper with a superior precision even at high operation speed
- Easy mounting to machine tools, conveyer, test stands e.g. SAUTER TVO-N, TVM-N etc.
- Zeroing, pre-added and pre-reduced length as well as switching the unit can be done manually
- Data interface RS-232 standard
- Selectable measuring units: mm, inch

### Technical data

- Dimensions housing W×D×H 77×43×34 mm
- Battery operation, batteries standard (3 V CR2032)

### Accessories

- RS-232/PC connection cable, SAUTER LB-A01, € 360,-
- Mounting the length measuring device LB onto a SAUTER test stand at the factory, SAUTER LB-A02, € 190,-

STANDARD				OPTION	
RS 232	ZERO	BATT	1 DAY	SOFTWARE	+4 DAYS

Model	Measuring range [Max] mm	Readout [d] mm	Direction of measurement	Price excl. of VAT ex works €	Option Factory calibration certificate	
					KERN	€
SAUTER LB 200-2	200	0,01	vertical	1050,-	961-150	132,-
LB 300-2	300	0,01	vertical	1150,-	961-150	132,-
LB 500-2	500	0,01	vertical	1250,-	961-150	132,-