





"Pen type" Leeb hardness tester for mobile hardness testing of metals

Features

- · User-friendly operation: The compact version enables the product to be used in a significantly wider range of applications compared with traditional devices
- The measuring device has been designed for one-hand operation and this allows the user to work more quickly and flexibly
- Modern LCD display: Optimised for industrial applications: increased luminosity and backlight can be switched on, that way the display can be read from any angle
- All measurement directions possible (360°) thanks to an automatic compensation function
- Internal impact sensor included (Type D)
- · Measurement value display: Rockwell (B & C), Vickers (HV), Brinell (HB), Leeb (HL) Hardness comparison block not included
- Internal data memory for up to 500 measurements with date and time
- · Data interface USB, including USB interface
- 11 Delivered in a robust carrying case

Technical data

- Measurement uncertainty ± 4 HLD
- · Minimum sample weight on a solid and stable support: 2 kg
- · Minimum sample material thickness: 3 mm with coupling on fixed base
- Dimensions W×D×H 35×25×145 mm
- · Operation by rechargeable battery, standard, operating time without backlight 16 h, charging time 3 h
- · Mains adapter, external, standard
- Net weight approx. 0,07 kg

Accessories

- · Plug-In for data transfer of measuring data from the measuring instrument and transfer to a PC, e.g. in Microsoft Excel®, SAUTER AFI-1.0, € 90,-
- · Impact body, SAUTER AHMO D01, € 115,-
- 2 Test block Type D/DC, Ø 90 mm (± 1 mm), Net weight < 3 kg, hardness range 790 ± 40 HL, SAUTER AHMO D02, € 190,-630 ± 40 HL, SAUTER AHMO D03, € 190,-530 ± 40 HL, SAUTER AHMO D04, € 190,-
- · Factory calibration certificates for SAUTER AHMO D02, AHMO D03, AHMO D04, SAUTER 961-132, € 132,-

















| OPTION | | |
|-----------|----------|---------|
| | | ISO |
| CAL BLOCK | SOFTWARE | +4 DAYS |

| Model | Sensor | Measuring range | Readout | Price | Option | |
|--------|--------|-----------------|---------|--------------|----------------------------------|-------|
| | | | | excl. of VAT | Factory calibration certificates | |
| | | [Max] | [d] | ex works | | |
| SAUTER | | HLD | HL | € | KERN | € |
| HN-D | Typ D | 170-960 | 1 | 860,- | 961-131 | 132,- |