

# CONTAINERCARRIER CC-2030-3-F



**Date tehnice**

Disponibil pentru

Greutate pe cui

Sarcina pe axa

Sarcina totala

Greutate proprie

Sarcina utila

Picioare sustinere

Inaltime cuplare

Inaltime sasiu

Dimensiune anvelope

Conexiune electrica


**Technische Daten**

Geeignet für

Sattellast

Max. Achslast per Achse

Gesamt zulässige Masse

Leergewicht

Nutzlast

Stützvorrichtung

Sattelhöhe

Chassishöhe

Reifengröße

Elektrische Anschlüsse


**Technical data**

Suitable for

Kingpin weight

Maximal Axleload / axle

Gross trailer weight

Empty weight

Payload

Landing gear

Fifthwheel height

Chassisheight

Tyresize

Electrical connectors

**CC-2030-3-F**

20 ft central

30 ft central

20 ft rear (optional)

12.000 kg

9.000 kg

39.000 kg

3.400 kg

35.600 kg

ALU 20.000 kg


1.180 mm

1.330 mm


385/65 R22,5


1x 15 pin

**OPTIUNI / OPTIONEN / OPTIONS**



**05-25**

**05-26**

**07-05**








**07-28**

**07-16/07-17**





**07-43/07-44**

**07-38**

**07-52**

**11-2-17**

**11-21**

**15-4-05**

**15-4-07**

**15-14**

**15-17**

**17-7**

**17-19**

**17-24**

**17-32**

**17-33**

**17-34**

**17-35**

**21-5**

**21-6/10/11/12**

**21-8/07-03**

**07-NS-12/ 13/14**

