




Standard: EN 61 238-1



**Connection tubes - GTY type**

**3** YEAR WARRANTY

Copper pipes with galvanic tin coating, used for joining of copper rigid or multicore conductors with different sections. The assembling is made by mechanical pressing with crimping tool.


**Technical data:**

- Material: copper alloy
- Coating: tin
- Application: general

Type	Length L (mm)	Outer diameter D (mm)	Inner diameter d (mm)	Cable (mm <sup>2</sup> )	Packing / Box (pcs)	Catalogue number
GTY-4	20	5	3	4	1000 / 16000	<b>59213</b>
GTY-6	25	5.3	3.7	6	500 / 1500 / 12000	<b>59201</b>
GTY-10	30	6.3	4.5	10	500 / 1500 / 12000	<b>59202</b>
GTY-16	35	7.5	5.7	16	100 / 200 / 4800	<b>59203</b>
GTY-25	40	9	7.2	25	100 / 500 / 2000	<b>59204</b>
GTY-35	45	10.8	8.5	35	100 / 200 / 1600	<b>59205</b>
GTY-50	50	12.5	9.8	50	20 / 200 / 1600	<b>59206</b>
GTY-70	55	14.5	11.5	70	10 / 100 / 800	<b>59207</b>
GTY-95	60	17	13.7	95	10 / 80 / 640	<b>59208</b>
GTY-120	65	19	15	120	10 / 60 / 480	<b>59209</b>
GTY-150	70	21	16.7	150	10 / 50 / 400	<b>59210</b>
GTY-185	75	23	18.5	185	10 / 40 / 320	<b>59211</b>
GTY-240	80	26	21	240	10 / 30 / 240	<b>59212</b>



Standard: EN 61 238-1



**Bimetallic connection tube - GTL type**

**3** YEAR WARRANTY

Pipes made of two metals – copper and aluminum without galvanic coating. They are designed for joining copper and aluminum conductors – rigid or multicore conductors with different section. The connection is accomplished through crimping pliers, through mechanical pressing of the butt terminals and the conductor. They are used for protection against electrochemical corrosion got at two metals contact with different chemical properties and conductivity at electrical current feed. They are manufactured under modern technology and have high quality and long exploitation period.

**Technical data:**

- Material: copper aluminum alloy
- Coating: none
- Application: general for joining of two types of conductors

Butt terminal type	d1	D1	d2	D2	l1	l2	L	Packing / Box (pcs)	Catalogue number
GTL - 16	5	9	6	10	30	30	75	20 / 200 / 1200	<b>59214</b>
GTL - 25	6	10	7	12	30	33	82	20 / 400 / 1500	<b>59215</b>
GTL - 35	7	11	8.5	14	30	40	90	20 / 300 / 1000	<b>59216</b>
GTL - 50	8.5	13	9.8	16	32	42	95	20 / 800	<b>59217</b>
GTL - 70	9.5	15	11.5	18	38	50	105	10 / 600	<b>59218</b>
GTL - 95	11.5	17	13.5	21	40	50	110	10 / 500	<b>59219</b>
GTL - 120	13.5	19	15	23	42	55	112	10 / 400	<b>59220</b>
GTL - 150	15	21	17	25	44	55	118	10 / 350	<b>59221</b>
GTL - 185	17	23	18.5	27	46	60	125	10 / 300	<b>59222</b>
GTL - 240	19	26	21	30	54	60	130	10 / 200	<b>59223</b>