



# Hydraulic punching pliers WK - 8 type



#### Functions

Cutting through openings in sheet metal with gauge up to 3mm without rotary motion

### **Technical data:**

- Piercing head turning at 360°
- Form of the cutting element: round
- Size of the cutting element: Ø 22, 27.5, 34.3, 40, 49, 60.8mm
- Piercing capacity:
  - - sheet metal 3mm openings up to Ø 30mm
  - □ sheet metal 2mm openings up to Ø 60mm
- Element pressing power: 80kN
- Thickness of the element: 25mm
- Weight of the instrument: 3.5 kg
- Used hydraulic oil: #15 (hydraulic oil with viscosity 15)
- Metal box for the instrument
- A set of congestion hoops for the hydraulic cylinder
- Additional set of cutting elements for cable glands Ø16, 20, 26.2, 32.5, 39, 51, 63 and a square for display devices 46.5x46.5, 68x68 (ordered additionally); Catalogue number 54002

Туре	Packing (pcs) / carton	Catalogue number
WK - 8	2	54000
Additional set	2	54002



## Hydraulic punching press SYK - 15 type



#### **Functions:**

Cutting through openings in sheet metal with gauge up to 3mm without rotary motion

### Technical data:

- Protracting piercing head supplied with a hose for the hydraulic oil that gives possibility for piercing openings everywhere on the metal surface
- Form of the cutting element:
  - round
- square
- Size of the cutting element:
  - square: 32x32mm
  - round openings: Ø 22, 27.5, 34.3, 40, 49, 60.8mm
- Piercing capacity:
  - □ sheet metal 3mm openings up to Ø 60.8mm
  - - sheet metal 2mm openings up to Ø 115.5mm
  - square opening up to 110x110mm
- Element pressing power: 15T
- Thickness of the element: 25mm
- Weight of the instrument: 11.5 kg
- Used hydraulic oil: #15 (hydraulic oil with viscosity 15)
- Metal box for the instrument
- A set of congestion hoops for the hydraulic cylinder
- Additional set of cutting elements for cable glands Ø16, 20, 26.2, 32.5, 39, 51, 63 and a square for display devices 46.5x46.5, 68x68 (ordered additionally); Catalogue number 54002

Туре	Packing (pcs) / carton	Catalogue number
SYK – 15	2	54001
Additional set	2	54002