



TECHNICAL DATA	
Weight:	0.22 kg
HEAT INSULATION CLASS H:	
356°F	(180°C)
Ambient temperature range:	
-22+140°F	(-30+60°C)
Available on request: Different Voltages - Different connectors.	
Inlet voltage fluctuations must not exceed $\pm 10\%$ of nominal voltage to obtain correct operation and long life of coils.	
CE approved	

X	Power (W)
200	20 Watt.

Y	Connections
H	DIN43650-ISO4400

Z	Voltage (V)	Resistance (Ω)	Current (A)	
	Nominal	20~25 °C	Cold Coil	Hot Coil
C	24V RAC	23.2 \pm 7 %	0.95	0.63
B	110V RAC	470 \pm 7 %	0.19	0.14
A	220V RAC	1910 \pm 7 %	0.09	0.07
F	10V DC	5.0 \pm 8 %	1.98	1.28
E	12V DC	7.5 \pm 7 %	1.66	1.06
M	14V DC	9.3 \pm 7 %	1.48	0.96
N	20V DC	20 \pm 7 %	0.99	0.65
D	24V DC	28.6 \pm 7 %	0.88	0.53
G	26V DC	34.2 \pm 7 %	0.77	0.52
J	28V DC	39.2 \pm 7 %	0.71	0.50
L	36V DC	64 \pm 7 %	0.56	0.36
H	48V DC	110 \pm 7 %	0.45	0.28