

HVACR Clesti ampermetrici

SC600 Series

Înzestrat cu mai multe caracteristici și măsurători decât oricare alt contor cu clemă din industria HVACR, seria SC600 este prevăzută cu un cap pivotant, suport de testare pentru o testare mai sigură și o curea magnetică.

- Contorul de vârf de linie
- Clemă cu cap rotativ
- Curea magnetică
- Depozitare plumb
- Ecran dublu
- Suport de prindere al clemelor
- Frecvența prin Leads & Clamps
- Iluminare cadran (SC640 și 660)
- Cleste iluminat (SC640 și 660)
- Lumina de fundal LCD (SC640 și 660)
- Rotatia fazelor (SC660)
- Temperatura duala Delta T (SC660)
- Compatibil cu telefon inteligent cu aplicația Job Link (SC660)

Transmitator JL2 obligatoriu



Dial Backlight Lights up Selector Switch for Poorly Lit Places (SC640/660)



SC620 Specificatii:

Functii:

Volts AC	600
Amps AC	400
Volts DC	600
μAmps DC	500
Ohms	50M
Microfarads	5000
Hz (clamp)	10 to 400
Hz (leads)	10 to 1M
Duty Cycle%	5 to 95
±.5°C	-34°C to 500°C
Baterie	9V, 200 h tip alkaline

Gama:

Cea mai buna precizie:
Cea mai buna rezolutie

1.2%±8 /0.0001
2.0%±10 /0.01
0.5%±2 /0.0001
1.0%±2 /0.1
1.0%±5 /0.1
3%±5 /0.001
0.1%±5 /0.1
0.1%±5 /0.1
2%±10 /0.1
±.5°C * /0.1

SC640 Specifications:

Measurement:	Range:
Volts AC	600
Amps AC	400
Volts DC	600
μAmps DC	500
Ohms	50M
Microfarads	5000
Hz (clamp)	10 to 400
Hz (leads)	10 to 1M
Duty Cycle %	5 to 95
±.5°C	-34°C to 500°C
Battery	9V, 100 hrs Tip Alkaline

Best Accuracy/:

Best Resolution
1.2%±8 /0.0001
2.0%±10 /0.01
0.5%±2 /0.0001
1.0%±2 /0.1
1.0%±5 /0.1
3%±5 /0.001
0.1%±5 /0.1
0.1%±5 /0.1
2%±10 /0.1
±.5°C * /0.1

SC660 Specifications

Measurement:	Range:	Best Accuracy/:	Best Resolution
Wireless	.35m to 30m		
Volts AC	600	1.2%±10 /0.0001	
Amps AC	400	2.0%±10 /0.01	
Volts DC	600	0.5%±5 /0.0001	
Amps DC	400	2.0%±10 /0.01	
μAmps DC	1000	1.0%±5 /0.1	
Ohms	50M	1.0%±5 /0.01	
Microfarads	10000	3%±5 /0.00001	
Hz (clamp)	10 to 400	0.1%±5 /0.1	
Hz (leads)	10 to 1M	0.1%±5 /0.01	
Duty Cycle %	5 to 95	2%±10 /0.1	
±.5°C	-50C to 1300°C	±.5°C * /0.1	
Phase Rot.	80±5 to 600VAC	1.5%±10 /0.1	
Battery	9V, 100 h tip alkaline (fara fundal sau wireless)		

System accuracy (SC660 meter + K Type thermocouple)
field calibration)

SC600 Series

Loaded ClampMeterLine



	SC620	SC640	SC660
RMS real		•	•
Telefon smart compatibil cu JOB Link App			•
Temp duala Delta T			•
Schimbarea fazelor			•
Volți AC/DC	•	•	•
Curent de intrare		•	•
Clema rotativa	•	•	•
Curea magnetica	•	•	•
Depozitare sonda	•	•	•
Ecran dual cu val max 5000	•	•	
Ecran dual cu val max 10000			•
Temperatura °F/°C	•	•	•
Capacitanta	•	•	•
Ciclul de lucru %	•	•	•
400 Amps AC	•	•	•
400 Amps DC			•
Micro amperi DC	•	•	•
Frecventa vis plumb/cleste	•	•	•
Tensiune fara contact	•	•	•
50 Mega Ohm with 0.1 Resolution	•	•	•
Continuitate	•	•	•
Test dioda	•	•	•
Asteptare	•	•	•
Suport sonda de prindere	•	•	•
Cadran de fundal		•	•
Cleste iluminat		•	•
Fundal LCD		•	•
Indicator terminare baterie	•	•	•
Baterie 9V, 100 h		•	•
Baterie 9V, 200 h	•		
Conformitate cu UL Editia 3	•	•	•