Micro Quick-Connect Couplings

Series ESMC single shut-off





Plugs with r	male thread						
Thread	○Hexagon	1		Thread Length	Plug Length	Weight/pc. g	Type No.
M 5	7	18		5	10	3	ESMC 5 NA
G 1/8"	11	20		7	10	6	ESMC 18 NA
Plugs with f	female thread	ł					
Thread	○Hexagon	1		Thread Length	Plug Length	Weight/pc. g	Type No.
M 5	7	17		5	10	3	ESMC 5 NI
G 1/8"	12	19		7	10	6	ESMC 18 NI
G 1/0	12	13		,	10	U	LSIVIC TO IVI
Plugs with h	hose barb						
3							
Hose i.D.		-1	d	Stem Length	Plug Length	Weight/pc. g	Type No.
3 mm		24	7	13	10	2	ESMC 3 S
4 mm		24	7	13	10	3	ESMC 4 S
5 mm		24	9	13	10	3	ESMC 5 S
For hose clips	type ZOS (@ p	age 106	6). type H	S (@ page 107)			
			_				
Plugs with p	plastic hose c	onnect	tion				
For Hose	○Hexagon	ı			Plug Length	Weight/pc. g	Type No.
3 x 4 mm	8	25			10	12	ESMC 34 SQ
3 x 5 mm	8	25			10	12	ESMC 3 SQ
4 x 6 mm	8	25			10	12	ESMC 4 SQ
Plugs with r	nut and bulkh	ead sc	rewing				
	^						
For Hose	○Hex.1 ○		1	Thread	Thread Length	Weight/pc. g	Type No.
3 x 4 mm 3 x 5 mm	12 12	11	38	M 7 x 0.5	17 mm 17 mm	23	ESMC 34 SQSV
4 x 6 mm	12	11	38 38	M 7 x 0.5 M 8 x 0.5	17 mm 17 mm	23 23	ESMC 35 SQSV ESMC 4 SQSV
4 X 0 IIIIII	12	12	30	IVI 6 X U.5	17 111111	23	ESIVIC 4 SQSV
Plugs with I	hose barb and	l bulkh	ead scr	ewing			
Hose i.D.	○Hex.1 ○		l I	Thread	Thread Length	Weight/pc. g	Type No.
3 mm	12	11	45	M 7 x 0.5	17 mm	21	ESMC 3 SSV
4 mm	12	11	45	M 7 x 0.5	17 mm	21	ESMC 4 SSV
5 mm	12	12	45	M 8 x 0.5	17 mm	21	ESMC 5 SSV
Special version	ns and versions	in hras	s hlank o	n request			
Special version	iis and versions	III bi as	3 DIGITIK U	ii request.			

