



## Carrier and conveyor belt roller TRK for medium loads - Steel tubing $\varnothing$ 50 / 60 / 80 mm

- **Axle:** Steel, bright-drawn, axle ends with threads, interior threads, spring axle or width across flat.
- **Bearing:** Model TRK 50, 60, 80 made of deep drawn steel sheet with deep groove ball bearing 6003 or 6202, choice of ZZ or RS.
- Please specify the exact model when ordering: Roller  $\varnothing$ , axle  $\varnothing$ , axle type, roller length (RL), installation length (EL) and axle length (AL).
- **Ordering example:**  
TRK/50x1,5/ST/A10/M10 EL= 300 mm or TRK/80x2/ST/A17/SW14 EL= 950 mm.
- **Application:** For driven and non-driven roller conveyors. Higher load, speed, and running smoothness than TRG.
- **Options:** With splash water protection for A12 + A15.
- For high speed A15; A17 (all-steel model).

### Additional models and prices on request

Order No.	Precision tubing D x W mm	Axle $\varnothing$ mm	External threads			Internal threads		Spring axle		Width across flats		
			M	AL = EL + mm	EL = RL + mm	M	EL = RL + mm	AL = EL + mm	EL = RL + mm	SW	AL = EL + mm	EL = RL + mm
TRK/40x1.5/ST/A12	40 x 1.5	12	M12	30	24	M8	10	20	-	10	20	10
TRK/50x1.5/ST/A8	50 x 1.5	8	M8	30	23	-	-	20	10	-	-	-
TRK/50x1.5/ST/A10	50 x 1.5	10	M10	30	22	M6	10	20	10	8	20	10
TRK/50x1.5/ST/A12	50 x 1.5	12	M12	30	24	M8	10	20	10	10	20	10
TRK/50x1.5/ST/A14	50 x 1.5	14	M14	40	26	M10	10	20	10	12	20	10
TRK/50x1.5/ST/A15	50 x 1.5	15	M15	40	26	M10	10	20	10	12	20	10
TRK/50x1.5/ST/A17	50 x 1.5	17	M16	40	26	M12	10	-	-	14	0	10
TRK/50x2/ST/A8	50 x 2.0	8	M8	30	23	-	-	20	10	-	-	-
TRK/50x2/ST/A10	50 x 2.0	10	M10	30	22	M6	10	20	10	8	20	10
TRK/50x2/ST/A12	50 x 2.0	12	M12	30	24	M8	10	20	10	10	20	10
TRK/50x2/ST/A14	50 x 2.0	14	M14	40	26	M10	10	20	10	12	20	10
TRK/50x2/ST/A15	50 x 2.0	15	M15	40	26	M10	10	20	10	12	20	10
TRK/50x2/ST/A17	50 x 2.0	17	M16	40	26	M12	10	-	-	14	20	10
TRK/60x2/ST/A10	60 x 2.0	10	M10	30	22	M6	10	20	10	8	20	10
TRK/60x2/ST/A12	60 x 2.0	12	M12	30	24	M8	10	20	10	10	20	10
TRK/60x2/ST/A14	60 x 2.0	14	M14	40	26	M10	10	20	10	12	20	10
TRK/60x2/ST/A15	60 x 2.0	15	M15	40	26	M10	10	20	10	12	20	10
TRK/60x2/ST/A17	60 x 2.0	17	M16	40	26	M12	10	-	-	14	20	10
TRK/80x2/ST/A12	80 x 2.0	12	M12	30	24	M8	10	20	10	10	20	10
TRK/80x2/ST/A14	80 x 2.0	14	M14	40	26	M10	10	20	10	12	20	10
TRK/80x2/ST/A15	80 x 2.0	15	M15	40	26	M10	10	20	10	12	20	10
TRK/80x2/ST/A17	80 x 2.0	17	M16	40	26	M12	10	-	-	14	20	10